

# STARTERSKIT SPRAYTEC

STARTER KIT WITH MS POLYMER SPRAY

ADHESIVE FOR THIN BONDS

Get started immediately, with Cleaner and gun

Glue everything

Single-sided application

Repositionable

Also on damp surfaces (hand dry)



## GENERAL INFORMATION

### Product description

Get this starter kit for gluing all larger surfaces.

SprayTec spray adhesive is safe on all materials. Thanks to the high glue strength of 15 kg/cm<sup>2</sup>, you can glue up to 5 m<sup>2</sup> of glue area per can.

With the included Spray & PUR Cleaner, you effortlessly clean the gun afterwards for the next use.

SprayTec contains no harmful solvents, isocyanates or phthalates.

Starter kit contents:

- 3 x ST7-101 SprayTec Large Surfaces
- 1 x Spray & PUR Cleaner
- 1 x Spray & PUR Gun
- 1 x Leaflet Starterskit SprayTec A4

### Available packages & colors

SKU	EAN	Description
530999000	5414195024386	Starterskit SprayTec

### Application

-

## TECHNICAL INFORMATION

### Specifications

### Technical data sheet

## Specifications SprayTec

All values at 23°C, 50% Relative humidity:

- Basis: MS Hybrid polymer.
- Curing mechanism: Polymerisation by (air) humidity.
- Colour: white.
- Tack build-up: 10-20 minutes.
- Skin formation: 30 minutes.
- Hand strength/functional strength: 4h.
- Curing: 24h.
- Adhesion strength\*: 15 kg/cm<sup>2</sup>.
- Processing temperature: +5°C to +40°C.
- Temperature resistance: -40°C to +100°C (peak max 30 minutes: 150°C).
- Adhesive thickness: 0.2 mm to 1 mm.
- Consumption: +/- 5 m<sup>2</sup>/can (0.25 mm adhesive thickness).
- Paintable with most lacquers and paints. Do not use in combination with alkyd resin paints.
- Shelf life: 18 months from production. The first seven digits of the batch number form the production date: YY WW DDD, where YY = year (19 = 2019), WW = week and DDD = day.
- Safety measures: refer to the latest published safety data sheet on the website.

(\* ) Adhesion strength measured as Tensile Lap Shear Strength, depending on substrate and substrate preparation.

## Specifications gun

- Type of gun: PU Foam.
- Material: Metal/plastic.
- Force transmission: Adjustable.
- Drip stop: no.
- Force control: no.
- Number of settings: 50.

## Specifications Cleaner

- Occurrence (at 20°C): liquid.
- Vapour pressure (at 20°C): >= 3000 hPa.
- Vapour pressure (at 50°C): >= 8000 hPa.
- Relative density (at 20°C): 0.79.
- Water solubility: soluble.
- Soluble in: ethanol, ether, chloroform.
- Relative vapour density: > 1.
- Shelf life: 24 months, dry, cool and frost-free.
- Safety measures: Please consult the safety data sheet.

[starterskit-spraytecnovatechtec2025-04-10-09-52-06en.pdf](#)

