

SUPER AKTIVATOR

ACTIVATES SUPER

- ▣ Allows bonding on porous surfaces
- ▣ Pressing components together no longer necessary
- ▣ Increases the filling capacity of Super



GENERAL INFORMATION

Product description

- ▣ Super Aktivator speeds up the curing of Super, making the adhesive even more versatile:
 - after treatment, Super hardens even in thicker layers and it is now also possible to glue porous materials.
 - It is the perfect combination of strength, bonding speed and security, simplicity and perfect durability.



Available packages & colors

SKU	EAN	Description
501105000	5414195003596	Super Aktivator - aerosol 200ml

Application

Allows also the bonding of porous materials, such as bluestone, chipboard, stone, etc. with Super.

TECHNICAL INFORMATION

Safety data sheet

[tec7-super-aktivator-sds-en-201203.pdf](#)

Technical data sheet

[super-aktivatornovatechtecv2020-03-09-13-47-15en.pdf](#)

INSTRUCTIONS

To bond:

- Apply only on one side of a clean, dry, grease and dust-free surface.
- Apply on the least porous surface.
- Apply a thin coat of Super on the other surface.
- Join together and let the Super harden.

To fill gaps:

- Use dry and clean sand or sawdust as possible fillers.
- Apply Super until the filler is saturated.
- Spray Super Aktivator from a distance of 30 cm.
- The filling can be sanded after curing. Fill deeper holes with multiple layers to avoid overreaction.