XILICON

SILICONE SPRAY

- Transparent dry-film lubrication
- Flawless protection
- Prevents sticking
- Water and moisture repelling

GENERAL INFORMATION

Product description

The applied film is extremely thin, clear, durable, non-flammable, odourless, smudge-proof and effective on: all metal, rubber, wood, leather, plastic, varnish, paint, fabric, vinyl, etc.

This dry lubricating film does not acidify, does not evaporate, does not harden and prevents freezing.

Due to its pure composition, it is pressure resistant up to 1400 kg/cm² and temperature resistant from -70°C to + 280°C.

Available packages & colors

	SKU	EAN	Description
	201012000	5414195010006	Xilicon - aerosol 400ml

Application

- Lubricates high tech mechanisms and moving parts.
- Protects electrical equipment, synthetic materials, rubber and metal.
- Prevents freezing and sticking of rubber sealings.
- Waterproofs textile, wood and leather.

TECHNICAL INFORMATION

Specifications

- Colour: colourless.
- Odour: slightly paraffin.
- Basis: pure silicone oil.
- Pressure resistance: 1,400 kg/cm².
- Heat-resistance: permanent from -70 °C to +250 °C, with peaks to +280 °C.
- Solubility: insoluble in water, soluble in aliphatic hydrocarbons.
- Shelf life: 36 months kept in a dry, cool and frost-free place.
- Safety measures: Please consult the safety data sheet.

Technical data sheet

xiliconnovatechtecv2024-03-18-15-51-42en.pdf

Safety data sheet

xilicon-aerosol-sds-en-251029.pdf

INSTRUCTIONS

Spray sparingly at a distance of +/-30 cm. Treated surfaces can be cleaned with Tec7 Cleaner and/or Multiclean.

© 2026 Tec7

Crafted by Brigada