

XILICON

SILICONE SPRAY

- ▣ Transparent dry-film lubrication
- ▣ Flawless protection
- ▣ Prevents sticking
- ▣ Water and moisture repelling



GENERAL INFORMATION

Product description

The applied film is extremely thin, clear, durable, non-flammable, odourless, smudge-proof and effective on: all metal, rubber, wood, leather, plastic, varnish, paint, fabric, vinyl, etc.

This dry lubricating film does not acidify, does not evaporate, does not harden and prevents freezing.

Due to its pure composition, it is pressure resistant up to 1400 kg/cm² and temperature resistant from -70°C to + 280°C.

Available packages & colors

SKU	EAN	Description
201012000	5414195010006	Xilicon - aerosol 400ml

Application

- Lubricates high tech mechanisms and moving parts.
- Protects electrical equipment, synthetic materials, rubber and metal.
- Prevents freezing and sticking of rubber sealings.
- Waterproofs textile, wood and leather.

TECHNICAL INFORMATION

Specifications

- Colour: colourless.
- Odour: slightly paraffin.
- Basis: pure silicone oil.
- Pressure resistance: 1,400 kg/cm².
- Heat-resistance: permanent from -70 °C to +250 °C, with peaks to +280 °C.
- Solubility: insoluble in water, soluble in aliphatic hydrocarbons.
- Shelf life: 36 months kept in a dry, cool and frost-free place.
- Safety measures: Please consult the safety data sheet.

Safety data sheet

[xilicon-aerosol-sds-en-220420.pdf](#)

Technical data sheet

[xiliconnovatechtecv2024-03-18-15-51-42en.pdf](#)

INSTRUCTIONS

Spray sparingly at a distance of +/-30 cm. Treated surfaces can be cleaned with Tec7 Cleaner and/or Multiclean.