

WP7-301 ROOFING WATERPROOF

ROOF REPAIR PASTE

Instantly waterproof and rain resistant.

Gold repair of leaks, cracks and blisters.

With rubber for lasting flexibility.

With bitumen for perfect sealing.

With fibers for permanent strength.



GENERAL INFORMATION

Product description

Roof Waterproof is a ready for use and easy to apply rubber, bitumen and glass fibre based roof repair product that can be used on both wet and dry surfaces. Also suitable for vertical applications, Roof Waterproof is immediately waterproof, rain resistant, adheres to most building materials and is also compatible with all bituminous materials. Roof Waterproof can also be used with slate for extra UV protection.



Available packages & colors

SKU	EAN	Description
602150296	5414195012321	WP7-301 Roofing Waterproof - cartridge 310ml
602205296	5414195012444	WP7-301 Roofing Waterproof- pot 4,4L
602206296	5414195016251	WP7-301 Roof Waterproof - 870ml
602207296	5414195016275	WP7-301 Roof 2.0 - 8,7L

Application

- Sealing leaks in bituminous roofs and in gutters.
- Repair of blisters and cracks.
- Sealing of passages and chimneys.
- Waterproofing of foundations (EN 15814 certified).
- Waterproofing of connections, eaves, domes, balconies and terraces.

TECHNICAL INFORMATION

Specifications

- Base: glass fiber filled modified bitumen.
- Odor: solvent odor.
- Colour black.
- Relative density: 1.1.
- Elongation at break: 170%.
- Application temperature: -15°C / + 40°C.
- Temperature resistance: -40°C / + 85°C.
- Chemical resistance: not resistant to hydrocarbon based solvents.
- Paintable: no.
- Shelf life: 24 months, in closed original packaging, dry, cool and frost-free.
- Safety measures: please consult the safety data sheet.

Technical data sheet

[wp7-301-roofing-waterproofnovatechtcv2025-03-21-11-44-51en-ie.pdf](#)

Safety data sheet

[wp7-301-sds-en-251001.pdf](#)

INSTRUCTIONS

- Apply on a clean and stable surface, free from ice or snow.
- If necessary, clean and dry (without heating), remove loose parts and hardened bitumen, cut blisters cross shape.
- Reinforce major repairs with pieces of roofing or a fibreglass tape.
- Apply with caulking gun, brush or spatula.

Finish and clean tools with Tec7 Cleaner. Do not use in ponds or watercourses, or on roofs that drain into ponds. Layer thickness 2mm, when finishing with slate stroke 1mm thickness is sufficient.

1 liter = 1 mm on 1 m².