

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



## MULTICLEAN

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : MULTICLEAN  
Registration number REACH : Not applicable (mixture)  
Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004  
Degreasing agent

##### 1.2.2 Uses advised against

No uses advised against

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

TEC7\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@tec7.be  
\*TEC7 is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.

#### 2.2. Label elements



**Signal word** Danger

**H-statements**  
H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

**P-statements**  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

#### 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

# MULTICLEAN

Caution! Substance is absorbed through the skin

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
2-butoxyethanol 01-2119475108-36	111-76-2 203-905-0	2.5% ≤C<10%	Acute Tox. 3; H331 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319	(1)(2)(10)	Constituent	ATE inhalation (vapour): 3 mg/l ATE oral: 1200 mg/kg
propan-2-ol 01-2119457558-25	67-63-0 200-661-7	1%≤C<2.5%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent	
butane 01-2119474691-32	106-97-8 203-448-7	2.5% ≤C<10%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	
propane 01-2119486944-21	74-98-6 200-827-9	2.5% ≤C<10%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
isobutane 01-2119485395-27	75-28-5 200-857-2	0.1%≤C<1% %	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	

- (1) For H- and EUH-statements in full: see section 16  
(2) Substance with a Community workplace exposure limit  
(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006  
(21) 1,3-butadiene <0.1%

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

If you feel unwell, consult a doctor/medical service.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water.

#### After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Central nervous system depression. Headache. Nausea. Disturbances of consciousness.

##### After skin contact:

No effects known.

##### After eye contact:

Redness of the eye tissue.

##### After ingestion:

Gastrointestinal complaints. Diarrhoea. Headache. Vomiting. Disturbances of consciousness.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Reason for revision: 3.2, 8, 15

Publication date: 2000-09-16

Date of revision: 2023-07-20

Revision number: 1102

BIG number: 32180

2 / 17

# MULTICLEAN

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

## 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

## 5.3. Advice for firefighters

### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.

### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034).

#### Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Keep container tightly closed.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Protect against frost. Keep out of direct sunlight. Keep container in a well-ventilated place. Fireproof storeroom. Meet the legal requirements.

#### 7.2.2 Keep away from:

Heat sources, ignition sources.

#### 7.2.3 Suitable packaging material:

Aerosol.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

#### EU

2-Butoxyethanol	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	98 mg/m <sup>3</sup>
	Short time value (Indicative occupational exposure limit value)	50 ppm
	Short time value (Indicative occupational exposure limit value)	246 mg/m <sup>3</sup>

#### Belgium

Reason for revision: 3.2, 8, 15

Publication date: 2000-09-16

Date of revision: 2023-07-20

Revision number: 1102

BIG number: 32180

3 / 17

# MULTICLEAN

2-Butoxyéthanol	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	98 mg/m <sup>3</sup>
	Short time value	50 ppm
	Short time value	246 mg/m <sup>3</sup>
Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m <sup>3</sup>
	Short time value	400 ppm
	Short time value	1000 mg/m <sup>3</sup>
Butane, tous isomères: iso-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm

## The Netherlands

2-Butoxyethanol	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	20.4 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	100 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	50 ppm
	Short time value (Public occupational exposure limit value)	246 mg/m <sup>3</sup>

## France

2-Butoxyéthanol	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	10 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	49 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	50 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	246 mg/m <sup>3</sup>
Alcool isopropylique	Short time value (VL: Valeur non réglementaire indicative)	400 ppm
	Short time value (VL: Valeur non réglementaire indicative)	980 mg/m <sup>3</sup>
n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m <sup>3</sup>

## Germany

2-Butoxyethanol	Time-weighted average exposure limit 8 h (TRGS 900)	10 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	49 mg/m <sup>3</sup>
Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
Isobutan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m <sup>3</sup>
Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	500 mg/m <sup>3</sup>

## Austria

2-Butoxyethanol	Tagesmittelwert (MAK)	20 ppm
	Tagesmittelwert (MAK)	98 mg/m <sup>3</sup>
	Kurzzeitwert 30(Miw) 4x (MAK)	40 ppm
	Kurzzeitwert 30(Miw) 4x (MAK)	200 mg/m <sup>3</sup>
2-Propanol Kurzzeitwert für Großguss	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m <sup>3</sup>
	Kurzzeitwert 30(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 30(Miw) 4x (MAK)	2000 mg/m <sup>3</sup>
2-Propanol	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m <sup>3</sup>
	Kurzzeitwert 15(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 mg/m <sup>3</sup>
Butan (beide Isomeren): n-Butan (R 600) Isobutan (R 600a)	Tagesmittelwert (MAK)	800 ppm
	Tagesmittelwert (MAK)	1900 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	1600 ppm

Reason for revision: 3.2, 8, 15

Publication date: 2000-09-16

Date of revision: 2023-07-20

Revision number: 1102

BIG number: 32180

4 / 17

# MULTICLEAN

Butan (beide Isomeren): n-Butan (R 600) Isobutan (R 600a)	Kurzzeitwert 60(Mow) 3x (MAK)	3800 mg/m <sup>3</sup>
Propan (R 290)	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1800 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m <sup>3</sup>

## UK

2-Butoxyethanol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	25 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	123 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	50 ppm
	Short time value (Workplace exposure limit (EH40/2005))	246 mg/m <sup>3</sup>
Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m <sup>3</sup>
Propan-2-ol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	999 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1250 mg/m <sup>3</sup>

## USA (TLV-ACGIH)

2-Butoxyethanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	20 ppm
2-propanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	400 ppm
Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm

## b) National biological limit values

If limit values are applicable and available these will be listed below.

### Germany

2-Butoxyethanol (Butoxyessigsäure (nach Hydrolyse))	Urin: expositionsende, bzw. schichtende bei langzeitexposition: nach mehreren vorangegangenen schichten	150 mg/g Kreatinin	
Propan-2-ol (Aceton)	Urin: expositionsende, bzw. schichtende	25 mg/l	
Propan-2-ol (Aceton)	Vollblut: expositionsende, bzw. schichtende	25 mg/l	

### UK

2-Butoxyethanol (butoxyacetic acid)	Urine: post shift	240 mmol/mol creatinine	
-------------------------------------	-------------------	-------------------------	--

### USA (BEI-ACGIH)

2-butoxyethanol (Butoxyacetic acid (BAA))	urine: end of shift	200 mg/g creatinine	With hydrolysis
2-Propanol (Acetone)	Urine: end of shift at end of workweek	40 mg/L	Background, Nonspecific

## 8.1.2 Sampling methods

Product name	Test	Number
2-Butoxyethanol (Alcohols IV)	NIOSH	1403
2-Butoxyethanol (Butyl Cellosolve solvent)	OSHA	83
2-Butoxyethanol	OSHA	5001
Butoxyacetic acid	NIOSH	8316
Butyl cellosolve (Volatile Organic compounds)	NIOSH	2549
Butyl Cellosolve	OSHA	83
Isopropanol (Volatile Organic compounds)	NIOSH	2549
Isopropyl Alcohol (Alcohols I)	NIOSH	1400
Isopropyl Alcohol	NIOSH	3900
Isopropyl Alcohol	OSHA	5001

## 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

## 8.1.4 Threshold values

### DNEL/DMEL - Workers

#### 2-butoxyethanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	98 mg/m <sup>3</sup>	
	Acute systemic effects inhalation	1091 mg/m <sup>3</sup>	
	Acute local effects inhalation	246 mg/m <sup>3</sup>	

Reason for revision: 3.2, 8, 15

Publication date: 2000-09-16

Date of revision: 2023-07-20

Revision number: 1102

BIG number: 32180

5 / 17

# MULTICLEAN

## propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	888 mg/kg bw/day	

## DNEL/DMEL - General population

### 2-butoxyethanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	59 mg/m <sup>3</sup>	
	Acute systemic effects inhalation	426 mg/m <sup>3</sup>	
	Acute local effects inhalation	147 mg/m <sup>3</sup>	
	Long-term systemic effects oral	6.3 mg/kg bw/day	
	Acute systemic effects oral	26.7 mg/kg bw/day	

## propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	

## PNEC

### 2-butoxyethanol

Compartments	Value	Remark
Fresh water	8.8 mg/l	
Marine water	0.88 mg/l	
Fresh water (intermittent releases)	26.4 mg/l	
STP	463 mg/l	
Fresh water sediment	34.6 mg/kg sediment dw	
Marine water sediment	3.46 mg/kg sediment dw	
Soil	2.33 mg/kg soil dw	
Oral	0.02 g/kg food	

### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

#### c) Eye protection:

Protective goggles (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Fruity odour
Odour threshold	No data available in the literature
Colour	Colourless
Particle size	No data available in the literature
Explosion limits	1.1 - 12 vol %
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	Not applicable (aerosol)
Kinematic viscosity	Not applicable (aerosol)
Melting point	No data available in the literature
Boiling point	No data available in the literature
Relative vapour density	> 1

# MULTICLEAN

Vapour pressure	No data available in the literature
Solubility	Water ; soluble
Relative density	0.94 ; 20 °C ; Liquid
Absolute density	938 kg/m <sup>3</sup> ; 20 °C ; Liquid
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	-97 °C
pH	10.4

## 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Basic reaction.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

#### Precautionary measures

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

#### Acute toxicity

#### MULTICLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

#### 2-butoxyethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	1746 mg/kg bw		Rat (male)	Experimental value	
Oral	LD50	OECD 401	1414 mg/kg bw		Guinea pig (male / female)	Experimental value	
Dermal	LC0	OECD 402	> 2000 mg/kg bw	24 h	Guinea pig (male / female)	Experimental value	
Inhalation (vapours)	ATE		3 mg/l			Annex VI	
Inhalation (saturated vapour)	Dose level	Equivalent to OECD 433	2.25 mg/l	4 h	Guinea pig (male / female)	Experimental value	No effect

#### propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	16400 ml/kg bw	24 h	Rabbit	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	6 h	Rat (male / female)	Experimental value	

#### Conclusion

Not classified for acute toxicity

#### Corrosion/irritation

#### MULTICLEAN

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 3.2, 8, 15

Publication date: 2000-09-16

Date of revision: 2023-07-20

Revision number: 1102

BIG number: 32180

7 / 17

# MULTICLEAN

## 2-butoxyethanol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405	24 h	24; 48; 72 hours	Rabbit	Experimental value	Single treatment with rinsing
Skin	Irritating	EU Method B.4	4 h	24; 48; 72 hours	Rabbit	Experimental value	

## propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		1; 2; 3; 4; 7; 10; 14 days	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

### Conclusion

Not classified as irritating to the skin  
 Not classified as irritating to the eyes  
 Not classified as irritating to the respiratory system

### Respiratory or skin sensitisation

#### MULTICLEAN

No (test)data on the mixture available  
 Judgement is based on the relevant ingredients

## 2-butoxyethanol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

## propan-2-ol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

### Conclusion

Not classified as sensitizing for skin  
 Not classified as sensitizing for inhalation

### Specific target organ toxicity

#### MULTICLEAN

No (test)data on the mixture available  
 Judgement is based on the relevant ingredients

## 2-butoxyethanol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (drinking water)	NOAEL	Equivalent to OECD 408	< 69 mg/kg bw/day		No effect	90 days (continuous)	Rat (male)	Experimental value
Oral (drinking water)	NOAEL	Equivalent to OECD 408	< 82 mg/kg bw/day		No effect	90 day(s)	Rat (female)	Experimental value
Dermal	NOAEL	Equivalent to OECD 411	> 150 mg/kg bw/day		No effect	13 weeks (5 days / week)	Rabbit (male / female)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	< 31 ppm		No effect	14 weeks (6h / day, 5 days / week)	Rat (female)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	62.5 ppm		No effect	14 weeks (6h / day, 5 days / week)	Rat (male)	Experimental value

## propan-2-ol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm		No adverse systemic effects	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)	Dose level	Equivalent to OECD 403	5000 ppm	Central nervous system	Drowsiness, dizziness	6 h	Rat (male / female)	Experimental value

### Conclusion

Not classified for subchronic toxicity

### Mutagenicity (in vitro)

Reason for revision: 3.2, 8, 15

Publication date: 2000-09-16

Date of revision: 2023-07-20

Revision number: 1102

BIG number: 32180

8 / 17



# MULTICLEAN

## MULTICLEAN

No (test) data on the mixture available

Judgement is based on the relevant ingredients

### 2-butoxyethanol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)		Experimental value	

### propan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	

## Mutagenicity (in vivo)

### MULTICLEAN

No (test) data on the mixture available

Judgement is based on the relevant ingredients

### 2-butoxyethanol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD 474	3 dose(s)/24-hour interval	Mouse (male)		Experimental value

### propan-2-ol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male / female)		Experimental value

### Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### MULTICLEAN

No (test) data on the mixture available

Judgement is based on the relevant ingredients

### 2-butoxyethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	> 125 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

### propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOEL	OECD 451	5000 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

### Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

### MULTICLEAN

No (test) data on the mixture available

Judgement is based on the relevant ingredients

# MULTICLEAN

## 2-butoxyethanol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEC	Equivalent to OECD 414	200 mg/kg bw/day	3 days (gestation, daily)	Rat	No effect		Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	3 days (gestation, daily)	Rat	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	Fertility Assessment	720 mg/kg bw/day		Mouse (male / female)	No effect		Experimental value

## propan-2-ol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	Equivalent to OECD 415	853 mg/kg bw/day		Rat (male / female)	No effect		Experimental value

### Conclusion

Not classified for reprotoxic or developmental toxicity

### Aspiration hazard

Judgement is based on the relevant ingredients  
Not classified for aspiration toxicity

### Toxicity other effects

#### MULTICLEAN

No (test)data on the mixture available

### Chronic effects from short and long-term exposure

#### MULTICLEAN

No effects known.

### 11.2. Information on other hazards

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

#### MULTICLEAN

No (test)data on the mixture available

Judgement of the mixture is based on the relevant ingredients

#### 2-butoxyethanol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	1474 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	1550 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	1840 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	286 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	Equivalent to OECD 204	> 100 mg/l	21 day(s)	Danio rerio	Semi-static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity aquatic crustacea	NOEC	OECD 211	100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	700 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Nominal concentration

# MULTICLEAN

## propan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	9640 mg/l - 10000 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	Toxicity threshold		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Long-term toxicity fish	NOELR	Petrotox computer model	> 1000 mg/l	28 day(s)	Brachydanio rerio			Estimated value
Long-term toxicity aquatic crustacea	NOEC		141 mg/l	16 day(s)	Daphnia magna		Fresh water	Experimental value; Growth
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	1050 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Toxicity test
	EC50	ISO 8192	41676 mg/l	30 minutes	Activated sludge			Experimental value

### Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

## 12.2. Persistence and degradability

### 2-butoxyethanol

#### Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	90 %; Carbon dioxide	28 day(s)	Experimental value

#### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.90	5.5 h	1.5E6 /cm <sup>3</sup>	QSAR

## propan-2-ol

#### Biodegradation water

Method	Value	Duration	Value determination
EU Method C.5	53 %; Oxygen consumption	5 day(s)	Experimental value

#### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	17.668 h	1.5E6 /cm <sup>3</sup>	Calculated value

### Conclusion

#### Water

The surfactant(s) is/are biodegradable according to Regulation (EC) No 648/2004

## 12.3. Bioaccumulative potential

### MULTICLEAN

#### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

## 2-butoxyethanol

#### Log Kow

Method	Remark	Value	Temperature	Value determination
BASF test		0.81	25 °C	Experimental value

## propan-2-ol

#### BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBFAF v3.01	1015			Estimated value

#### Log Kow

Method	Remark	Value	Temperature	Value determination
		0.05	25 °C	Weight of evidence approach

### Conclusion

Does not contain bioaccumulative component(s)

## 12.4. Mobility in soil

# MULTICLEAN

## 2-butoxyethanol

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.5 - 0.9	Calculated value

### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level I	0.31 %	0 %	0.01 %	0.59 %	99.09 %	QSAR

## propan-2-ol

### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.185 - 0.541	Calculated value

### **Conclusion**

Contains component(s) with potential for mobility in the soil

### **12.5. Results of PBT and vPvB assessment**

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

### **12.6. Endocrine disrupting properties**

No evidence of endocrine disrupting properties

### **12.7. Other adverse effects**

## MULTICLEAN

### **Greenhouse gases**

Contains component(s) included in the list of substances which may contribute to the greenhouse effect (IPCC)  
None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

### **Ozone-depleting potential (ODP)**

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

### **Groundwater**

Groundwater pollutant

### **Water ecotoxicity pH**

pH shift

## 2-butoxyethanol

### **Groundwater**

Groundwater pollutant

## propan-2-ol

### **Groundwater**

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### **13.1. Waste treatment methods**

#### **13.1.1 Provisions relating to waste**

##### **European Union**

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.  
Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

14 06 03\* (waste organic solvents, refrigerants and foam/aerosol propellants: other solvents and solvent mixtures). Depending on branch of industry and production process, also other waste codes may be applicable.

#### **13.1.2 Disposal methods**

Remove waste in accordance with local and/or national regulations. Specific treatment. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Should not be landfilled with household waste. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### **13.1.3 Packaging/Container**

##### **European Union**

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### **Road (ADR)**

#### **14.1. UN number**

UN number 1950

#### **14.2. UN proper shipping name**

Proper shipping name aerosols

#### **14.3. Transport hazard class(es)**

Reason for revision: 3.2, 8, 15

Publication date: 2000-09-16

Date of revision: 2023-07-20

Revision number: 1102

BIG number: 32180

12 / 17

# MULTICLEAN

Hazard identification number	
Class	2
Classification code	5F
<b>14.4. Packing group</b>	
Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Rail (RID)

<b>14.1. UN number</b>	
UN number	1950
<b>14.2. UN proper shipping name</b>	
Proper shipping name	aerosols
<b>14.3. Transport hazard class(es)</b>	
Hazard identification number	23
Class	2
Classification code	5F
<b>14.4. Packing group</b>	
Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Inland waterways (ADN)

<b>14.1. UN number/ID number</b>	
UN number/ID number	1950
<b>14.2. UN proper shipping name</b>	
Proper shipping name	aerosols
<b>14.3. Transport hazard class(es)</b>	
Class	2
Classification code	5F
<b>14.4. Packing group</b>	
Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Sea (IMDG/IMSBC)

<b>14.1. UN number</b>	
UN number	1950
<b>14.2. UN proper shipping name</b>	
Proper shipping name	aerosols
<b>14.3. Transport hazard class(es)</b>	
Class	2.1
<b>14.4. Packing group</b>	
Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Marine pollutant	-

# MULTICLEAN

Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable

## Air (ICAO-TI/IATA-DGR)

14.1. UN number/ID number	
UN number/ID number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
16 %	
146 g/l	

#### 2-butoxyethanol

Product name	Skin resorption
2-Butoxyethanol	Skin

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

Ingredients according to Regulation (EC) No 648/2004 and amendments

5-15% aliphatic hydrocarbons, perfumes, limonene

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· 2-butoxyethanol · propan-2-ol	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and,

Reason for revision: 3.2, 8, 15

Publication date: 2000-09-16

Date of revision: 2023-07-20

Revision number: 1102

BIG number: 32180

14 / 17

# MULTICLEAN

	development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	<p>— present an aspiration hazard and are labelled with H304,</p> <p>4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).</p> <p>5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:</p> <p>a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: “Keep lamps filled with this liquid out of the reach of children”; and, by 1 December 2010, “Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage”;</p> <p>b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: “Just a sip of grill lighter may lead to life threatening lung damage”;</p> <p>c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.</p>
· propan-2-ol	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	<p>1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:</p> <ul style="list-style-type: none"> <li>— metallic glitter intended mainly for decoration,</li> <li>— artificial snow and frost,</li> <li>— “whoopee” cushions,</li> <li>— silly string aerosols,</li> <li>— imitation excrement,</li> <li>— horns for parties,</li> <li>— decorative flakes and foams,</li> <li>— artificial cobwebs,</li> <li>— stink bombs.</li> </ul> <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: “For professional users only”.</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>
· 2-butoxyethanol · propan-2-ol	Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex. The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081

## National legislation Belgium

### MULTICLEAN

No data available

### 2-butoxyethanol

Résorption peau

2-Butoxyéthanol; D; La mention “D” signifie que la résorption de l’agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l’exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l’agent dans l’air.

Reason for revision: 3.2, 8, 15

Publication date: 2000-09-16

Date of revision: 2023-07-20

Revision number: 1102

BIG number: 32180

15 / 17

# MULTICLEAN

## propan-2-ol

Agents cancérogènes, mutagènes et reprotoxiques (Code du bien-être au travail, Livre VI, titre 2)	alcool isopropylique; VI.2.2.; Liste des procédés au cours desquels une substance ou un mélange se dégage; Procédé à l'acide fort dans la fabrication d'alcool isopropylique.
---	---

## **National legislation The Netherlands**

### MULTICLEAN

Waterbezwaarlijkheid	B (3); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

### 2-butoxyethanol

Huidopname (wettelijk)	2-Butoxyethanol; H
------------------------	--------------------

## **National legislation France**

### MULTICLEAN

No data available

### 2-butoxyethanol

Risque de pénétration percutanée	2-Butoxyéthanol; Risque de pénétration percutanée
----------------------------------	---

## **National legislation Germany**

### MULTICLEAN

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
-----------------------	-------------------------------------

WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
-----	--

### 2-butoxyethanol

TA-Luft	5.2.5
---------	-------

TRGS900 - Risiko der Fruchtschädigung	2-Butoxyethanol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	--

Hautresorptive Stoffe	2-Butoxyethanol; H; Hautresorptiv
-----------------------	-----------------------------------

## propan-2-ol

TA-Luft	5.2.5
---------	-------

TRGS900 - Risiko der Fruchtschädigung	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
---------------------------------------	--

## **National legislation Austria**

### MULTICLEAN

No data available

### 2-butoxyethanol

besondere Gefahr der Hautresorption	2-Butoxyethanol; H
-------------------------------------	--------------------

## **National legislation United Kingdom**

### MULTICLEAN

No data available

### 2-butoxyethanol

Skin absorption	2-Butoxyethanol; Sk
-----------------	---------------------

## **Other relevant data**

### MULTICLEAN

No data available

### 2-butoxyethanol

TLV - Carcinogen	2-Butoxyethanol; A3
------------------	---------------------

IARC - classification	3; 2-butoxyethanol
-----------------------	--------------------

## propan-2-ol

TLV - Carcinogen	2-propanol; A4
------------------	----------------

IARC - classification	3; Isopropanol
-----------------------	----------------

## **15.2. Chemical safety assessment**

No chemical safety assessment is required for a mixture.

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under section 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H336 May cause drowsiness or dizziness.

(\*) INTERNAL CLASSIFICATION BY BIG  
ADI Acceptable daily intake

Reason for revision: 3.2, 8, 15

Publication date: 2000-09-16

Date of revision: 2023-07-20

Revision number: 1102

BIG number: 32180

16 / 17



# MULTICLEAN

AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
LC0	Lethal Concentration 0 %
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.