

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



## GT7 AEROSOL

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : GT7 AEROSOL  
Registration number REACH : Not applicable (mixture)  
Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Lubricating oil

##### 1.2.2 Uses advised against

No uses advised against

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

TEC7\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@tec7.be  
\*TEC7 is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.

#### 2.2. Label elements



**Signal word** Danger

**H-statements**  
H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

**P-statements**  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

#### 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard  
Caution! Substance is absorbed through the skin

# GT7 AEROSOL

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
butane 01-2119474691-32	106-97-8 203-448-7	C≤40%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119457273-39	918-481-9	C≤30%	Asp. Tox. 1; H304 EUH066	(1)(10)	Constituent	
propane 01-2119486944-21	74-98-6 200-827-9	C≤30%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
white mineral oil (petroleum) 01-2119487078-27	8042-47-5 232-455-8	C≤20%	Asp. Tox. 1; H304	(1)(2)(10)	Constituent	

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

(21) 1,3-butadiene <0.1%

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

If you feel unwell, consult a doctor/medical service.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water.

#### After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

No effects known.

##### After skin contact:

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin.

##### After eye contact:

No effects known.

##### After ingestion:

No effects known.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

### 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

Reason for revision: 8; 15

Publication date: 2022-08-17

Date of revision: 2023-06-23

Revision number: 0704

BIG number: 44875

2 / 14

# GT7 AEROSOL

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.

## 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Protect against frost. Keep out of direct sunlight.

#### 7.2.2 Keep away from:

Heat sources, ignition sources.

#### 7.2.3 Suitable packaging material:

Aerosol.

#### 7.2.4 Non suitable packaging material:

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

#### Belgium

Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Huiles minérales (brouillards)	Time-weighted average exposure limit 8 h	5 mg/m <sup>3</sup>
	Short time value	10 mg/m <sup>3</sup>
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm

#### The Netherlands

Olienevel (minerale olie)	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	5 mg/m <sup>3</sup>
---------------------------	---	---------------------

#### France

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
----------	--	---------

Reason for revision: 8; 15

Publication date: 2022-08-17

Date of revision: 2023-06-23

Revision number: 0704

BIG number: 44875

3 / 14

# GT7 AEROSOL

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m <sup>3</sup>
----------	--	------------------------

## Germany

Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m <sup>3</sup>
Weißes Mineralöl (Erdöl)	Time-weighted average exposure limit 8 h (TRGS 900)	5 mg/m <sup>3</sup>

## Austria

Butan (beide Isomeren): n-Butan (R 600) Isobutan (R 600a)	Tagesmittelwert (MAK)	800 ppm
	Tagesmittelwert (MAK)	1900 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	1600 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3800 mg/m <sup>3</sup>
Propan (R 290)	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1800 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m <sup>3</sup>

## UK

Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m <sup>3</sup>

## USA (TLV-ACGIH)

Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm
Mineral oil, excluding metal working fluids: Pure, highly and severely refined	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m <sup>3</sup> (I)

(I): Inhalable fraction

### b) National biological limit values

If limit values are applicable and available these will be listed below.

#### 8.1.2 Sampling methods

Product name	Test	Number
Oil Mist (Mineral)	NIOSH	5026

#### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

#### 8.1.4 Threshold values

##### DNEL/DMEL - Workers

white mineral oil (petroleum)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	164.56 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	217.05 mg/kg bw/day	

##### DNEL/DMEL - General population

white mineral oil (petroleum)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	34.78 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	93.02 mg/kg bw/day	
	Long-term systemic effects oral	25 mg/kg bw/day	

#### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

Reason for revision: 8; 15

Publication date: 2022-08-17

Date of revision: 2023-06-23

Revision number: 0704

BIG number: 44875

4 / 14

# GT7 AEROSOL

Materials	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

**c) Eye protection:**

Protective goggles (EN 166).

**d) Skin protection:**

Protective clothing (EN 14605 or EN 13034).

**8.2.3 Environmental exposure controls:**

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available in the literature
Colour	Light yellow to light brown
Particle size	Not applicable (aerosol)
Explosion limits	0.7 - 9.5 vol % ; Propellant
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	1 mPa.s ; 20 °C ; Liquid
Kinematic viscosity	1 mm <sup>2</sup> /s ; 40 °C ; Liquid
Melting point	Not applicable (aerosol)
Boiling point	No data available in the literature
Relative vapour density	> 1
Vapour pressure	8530 hPa ; 20 °C ; Propellant
Solubility	Water ; insoluble
Relative density	0.81 ; 20 °C ; Liquid
Absolute density	810 kg/m <sup>3</sup> ; 20 °C ; Liquid
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
pH	Not applicable (non-soluble in water)

### 9.2. Other information

Evaporation rate	0.04 ; Butyl acetate ; Liquid
------------------	-------------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

**Precautionary measures**

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

**Acute toxicity**

GT7 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 8; 15

Publication date: 2022-08-17

Date of revision: 2023-06-23

Revision number: 0704

BIG number: 44875

5 / 14

# GT7 AEROSOL

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 15000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 3160 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 6.1 mg/l air	4 h	Rat (male / female)	Read-across	
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5.6 mg/l	4 h	Rat (male / female)	Read-across	

white mineral oil (petroleum)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5 mg/l	4 h	Rat (male / female)	Read-across	

## Conclusion

Not classified for acute toxicity

## Corrosion/irritation

### GT7 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment without rinsing
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

white mineral oil (petroleum)

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment
Skin	Not irritating	Equivalent to OECD 404	24 week(s)	24; 48; 72 hours	Rabbit	Read-across	

## Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

Not classified as irritating to the respiratory system

## Respiratory or skin sensitisation

### GT7 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male / female)	Read-across	

white mineral oil (petroleum)

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male)	Read-across	

## Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

## Specific target organ toxicity

### GT7 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 8; 15

Publication date: 2022-08-17

Date of revision: 2023-06-23

Revision number: 0704

BIG number: 44875

6 / 14

# GT7 AEROSOL

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	EPA OPP 82-1	≥ 500 mg/kg bw/day		No adverse systemic effects	13 weeks (7 days / week)	Rat (male / female)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	NOAEC systemic effects	Equivalent to OECD 413	6000 mg/m <sup>3</sup> air		No adverse systemic effects	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

white mineral oil (petroleum)

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (diet)	NOAEL	OECD 453	≥ 1200 mg/kg bw/day		No effect	24 month(s)	Rat (male / female)	Read-across
Dermal	NOAEL systemic effects	OECD 411	≥ 2000 mg/kg bw/day		No adverse systemic effects	13 weeks (daily)	Rat (male / female)	Read-across
Dermal	NOAEL local effects	OECD 411	< 125 mg/kg bw/day	Skin	No effect	13 weeks (daily)	Rat (male / female)	Read-across
Inhalation (aerosol)	NOEL	Equivalent to OECD 412	50 mg/m <sup>3</sup>	Lungs	No effect	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across
Inhalation (aerosol)	LOEL	Equivalent to OECD 412	210 mg/m <sup>3</sup>	Lungs	Weight changes	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

## Conclusion

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

GT7 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S. typhimurium and E. coli)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Human lymphocytes	No effect	Experimental value	

white mineral oil (petroleum)

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation	Equivalent to OECD 471	Bacteria (S. typhimurium)	No effect	Read-across	
Negative with metabolic activation, negative without metabolic activation	OECD 473	Chinese hamster ovary (CHO)	No effect	Read-across	

## Mutagenicity (in vivo)

GT7 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (stomach tube))	Equivalent to OECD 474		Mouse (male / female)		Experimental value

white mineral oil (petroleum)

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	OECD 474		Mouse (male / female)	Bone marrow	Read-across

## Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

GT7 AEROSOL

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 8; 15

Publication date: 2022-08-17

Date of revision: 2023-06-23

Revision number: 0704

BIG number: 44875

7 / 14

# GT7 AEROSOL

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOAEL	Carcinogenic toxicity study	50 %	52 week(s)	Mouse (male)	No carcinogenic effect		Experimental value

white mineral oil (petroleum)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (aerosol)	Dose level	Carcinogenic toxicity study	100 mg/m <sup>3</sup>	68 weeks (6h / day, 7 days / week)	Mouse (male)	No carcinogenic effect		Read-across
Dermal	NOEL	OECD 453	≥ 75 µl/week	104 weeks (3 times / week)	Mouse (male)	No carcinogenic effect		Read-across
Oral (diet)	NOAEL	OECD 453	≥ 1200 mg/kg bw/day	24 month(s)	Rat (male / female)	No carcinogenic effect		Read-across

## Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

### GT7 AEROSOL

No (test) data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	≥ 5220 mg/m <sup>3</sup> air	10 days (gestation, daily)	Rat	No effect		Read-across
Maternal toxicity (Oral (stomach tube))	NOAEC	Equivalent to OECD 414	≥ 5220 mg/m <sup>3</sup> air	10 day(s)	Rat	No effect		Read-across

white mineral oil (petroleum)

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	> 5000 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect		Read-across
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	> 5000 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect		Read-across
Effects on fertility (Dermal)	NOAEL	Equivalent to OECD 415	≥ 2000 mg/kg bw/day	≥ 13 weeks (5 days / week)	Rat (male / female)	No effect		Read-across

## Conclusion

Not classified for reprotoxic or developmental toxicity

## Aspiration hazard

Judgement is based on the relevant ingredients

Not classified for aspiration toxicity

## Toxicity other effects

### GT7 AEROSOL

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Skin				Skin	Skin dryness or cracking			Literature study

## Chronic effects from short and long-term exposure

### GT7 AEROSOL

No effects known.

## 11.2. Information on other hazards

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

#### GT7 AEROSOL

No (test) data on the mixture available

Judgement of the mixture is based on the relevant ingredients

Reason for revision: 8; 15

Publication date: 2022-08-17

Date of revision: 2023-06-23

Revision number: 0704

BIG number: 44875

8 / 14



# GT7 AEROSOL

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 1000 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	OECD 202	> 1000 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	EL50	OECD 201	> 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
	NOELR	OECD 201	1000 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Toxicity aquatic micro-organisms	EL50		> 1000 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR

white mineral oil (petroleum)

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 100 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	LC50	OECD 202	> 100 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	NOEL	OECD 201	≥ 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Weight of evidence; Growth rate
Long-term toxicity fish	NOEL		≥ 1000 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR
Long-term toxicity aquatic crustacea	NOEL	Equivalent to OECD 211	10 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Read-across; GLP

## Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

## 12.2. Persistence and degradability

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	80 %; GLP	28 day(s)	Read-across

### Biodegradation soil

Method	Value	Duration	Value determination
Equivalent to OECD 304A	60 % - 63 %; Oxygen consumption	61 day(s)	Read-across

white mineral oil (petroleum)

### Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	31 %; GLP	28 day(s)	Read-across

## Conclusion

### Water

Contains non readily biodegradable component(s)

## 12.3. Bioaccumulative potential

GT7 AEROSOL

### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### Log Kow

Method	Remark	Value	Temperature	Value determination
		3.2 - 7.2		Estimated value

white mineral oil (petroleum)

### BCF other aquatic organisms

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBAF v3.01	1216 l/kg; Fresh weight			Estimated value

### Log Kow

Method	Remark	Value	Temperature	Value determination
		5.2		Experimental value

## Conclusion

Reason for revision: 8; 15

Publication date: 2022-08-17

Date of revision: 2023-06-23

Revision number: 0704

BIG number: 44875

9 / 14

# GT7 AEROSOL

Contains bioaccumulative component(s)

## 12.4. Mobility in soil

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

(log) Koc

Parameter	Method	Value	Value determination
log Koc		4.2	Read-across

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	66 %	0 %	23 %	9.6 %	1.7 %	Calculated value

white mineral oil (petroleum)

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	2.6	Calculated value

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Fugacity Model Level III	32 %		0.87 %	1.3 %	66 %	Calculated value

## Conclusion

Contains component(s) that adsorb(s) into the soil

Contains component(s) with potential for mobility in the soil

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

GT7 AEROSOL

### Greenhouse gases

Contains component(s) included in the list of substances which may contribute to the greenhouse effect (IPCC)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### Groundwater

Groundwater pollutant

white mineral oil (petroleum)

### Groundwater

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

13 02 05\* (waste engine, gear and lubricating oils: mineral-based non-chlorinated engine, gear and lubricating oils). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste.

Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Specific treatment. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

#### 14.1. UN number

Reason for revision: 8; 15

Publication date: 2022-08-17

Date of revision: 2023-06-23

Revision number: 0704

BIG number: 44875

10 / 14

# GT7 AEROSOL

UN number	1950
<b>14.2. UN proper shipping name</b>	
Proper shipping name	aerosols
<b>14.3. Transport hazard class(es)</b>	
Hazard identification number	
Class	2
Classification code	5F
<b>14.4. Packing group</b>	
Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Rail (RID)

<b>14.1. UN number</b>	
UN number	1950
<b>14.2. UN proper shipping name</b>	
Proper shipping name	aerosols
<b>14.3. Transport hazard class(es)</b>	
Hazard identification number	23
Class	2
Classification code	5F
<b>14.4. Packing group</b>	
Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Inland waterways (ADN)

<b>14.1. UN number/ID number</b>	
UN number/ID number	1950
<b>14.2. UN proper shipping name</b>	
Proper shipping name	aerosols
<b>14.3. Transport hazard class(es)</b>	
Class	2
Classification code	5F
<b>14.4. Packing group</b>	
Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Sea (IMDG/IMSBC)

<b>14.1. UN number</b>	
UN number	1950
<b>14.2. UN proper shipping name</b>	
Proper shipping name	aerosols
<b>14.3. Transport hazard class(es)</b>	
Class	2.1
<b>14.4. Packing group</b>	

# GT7 AEROSOL

Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Marine pollutant	-
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
<b>14.7. Maritime transport in bulk according to IMO instruments</b>	
Annex II of MARPOL 73/78	Not applicable

## Air (ICAO-TI/IATA-DGR)

<b>14.1. UN number/ID number</b>	
UN number/ID number	1950
<b>14.2. UN proper shipping name</b>	
Proper shipping name	aerosols, flammable
<b>14.3. Transport hazard class(es)</b>	
Class	2.1
<b>14.4. Packing group</b>	
Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	A145
Special provisions	A167
Special provisions	A802
<b>Passenger and cargo transport</b>	
Limited quantities: maximum net quantity per packaging	30 kg G

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
84 %	
542 g/l	

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

European drinking water standards (98/83/EC and 2020/2184)

white mineral oil (petroleum)

Parameter	Parametric value	Note	Reference
Pesticides	0.1 µg/l		Listed in Annex I, Part B, of Directive (EU) 2020/2184 on the quality of water intended for human consumption.
Pesticides — Total	0.5 µg/l		Listed in Annex I, Part B, of Directive (EU) 2020/2184 on the quality of water intended for human consumption.

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics · white mineral oil (petroleum)	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even

Reason for revision: 8; 15

Publication date: 2022-08-17

Date of revision: 2023-06-23

Revision number: 0704

BIG number: 44875

12 / 14

# GT7 AEROSOL

types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: “Keep lamps filled with this liquid out of the reach of children”; and, by 1 December 2010, “Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage”; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: “Just a sip of grill lighter may lead to life threatening lung damage”; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
---	--

## National legislation Belgium

### GT7 AEROSOL

No data available

### white mineral oil (petroleum)

Agents cancérogènes, mutagènes et reprotoxiques (Code du bien-être au travail, Livre VI, titre 2)	huiles minérales; VI.2.2.; Liste des procédés au cours desquels une substance ou un mélange se dégage; Travaux entraînant une exposition cutanée à des huiles minérales qui ont été auparavant utilisées dans des moteurs à combustion interne pour lubrifier et refroidir les pièces mobiles du moteur.
---	--

## National legislation The Netherlands

### GT7 AEROSOL

Waterbezwaarlijkheid	B (2); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

## National legislation France

### GT7 AEROSOL

No data available

## National legislation Germany

### GT7 AEROSOL

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
TA-Luft	5.2.5
white mineral oil (petroleum)	
TA-Luft	5.2.5/I
TRGS900 - Risiko der Fruchtschädigung	Weißes Mineralöl (Erdöl); Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

## National legislation Austria

### GT7 AEROSOL

No data available

## National legislation United Kingdom

### GT7 AEROSOL

No data available

## Other relevant data

### GT7 AEROSOL

No data available

### white mineral oil (petroleum)

TLV - Carcinogen	Mineral oil, excluding metal working fluids: Pure, highly and severely refined; A4
------------------	--

## 15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under section 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(\*) INTERNAL CLASSIFICATION BY BIG

Reason for revision: 8; 15

Publication date: 2022-08-17

Date of revision: 2023-06-23

Revision number: 0704

BIG number: 44875

13 / 14

# GT7 AEROSOL

ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
LC0	Lethal Concentration 0 %
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.