

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



Poxy Primer B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Poxy Primer B
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Sealing compound

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

TEC7*
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@tec7.be
*TEC7 is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Skin Sens.	category 1	H317: May cause an allergic skin reaction.
Skin Corr.	category 1	H314: Causes severe skin burns and eye damage.
Eye Dam.	category 1	H318: Causes serious eye damage.
Aquatic Acute	category 1	H400: Very toxic to aquatic life.
Aquatic Chronic	category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2. Label elements



Contains: 3-butoxypropan-2-ol; m-phenylenebis(methylamine); reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane.

Signal word Danger

H-statements

H317 May cause an allergic skin reaction.
H314 Causes severe skin burns and eye damage.
H410 Very toxic to aquatic life with long lasting effects.

P-statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P280 Wear protective gloves, protective clothing and eye protection/face protection.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

<http://www.big.be>

© BIG vzw

Reason for revision: 8

Revision number: 0001

Publication date: 2023-08-23

Date of revision: 2023-11-28

BIG number: 69331

1 / 18

878-16433-054-en

Poxy Primer B

P260	Do not breathe vapours/mist.
P264	Wash hands thoroughly after handling.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.

2.3. Other hazards

Caution! Substance is absorbed through the skin

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
3-butoxypropan-2-ol 01-2119475527-28	5131-66-8 225-878-4	C<50%	Skin Irrit. 2; H315 Eye Irrit. 2; H319	(1)(10)	Constituent	
benzyl alcohol 01-2119492630-38	100-51-6 202-859-9	12.5% <C<25%	Acute Tox. 4; H332 Acute Tox. 4; H302 Eye Irrit. 2; H319	(1)(2)(6)(10)	Constituent	ATE oral: 1200 mg/kg
formaldehyde, polymer with m-phenylenebis(methylamine) and phenol	57214-10-5	12.5% <C<25%	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(10)	Constituent	
m-phenylenebis(methylamine) 01-2119480150-50	1477-55-0 216-032-5	5%<C<10%	Skin Sens. 1B; H317 Acute Tox. 4; H332 Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412 EUH071	(1)(2)(10)	Constituent	
reaction products of ethylenediamine and 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)]bisoxirane 01-2120766318-46	72480-18-3	2.5%<C<5%	Skin Sens. 1; H317 Acute Tox. 4; H302 Skin Corr. 1; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)	Constituent	M: 1 (Acute, BIG) M: 1 (Chronic, BIG)

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. Immediately consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately for 30 minutes with (lukewarm) water. Cut clothing; never remove burnt clothing from the wound. Do not give any pain medication. Consult a doctor/medical service.

After eye contact:

Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a doctor/medical service.

After ingestion:

Rinse mouth with water. Immediately consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Corrosion of the upper respiratory tract.

After skin contact:

Caustic burns/corrosion of the skin.

After eye contact:

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

2 / 18

Poxy Primer B

Corrosion of the eye tissue.

After ingestion:

Burns to the gastric/intestinal mucosa. Possible esophageal perforation.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.

Major fire: Class B foam (alcohol-resistant), Water spray if puddle cannot expand.

5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.

Major fire: Water; risk of puddle expansion.

5.2. Special hazards arising from the substance or mixture

On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide).

5.3. Advice for firefighters

5.3.1 Instructions:

Dilute toxic gases with water spray. Take account of toxic/corrosive precipitation water. Take account of toxic fire-fighting water. Use water moderately and if possible collect or contain it. Heat exposure: dilute toxic gas/vapour with water spray.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Face shield (EN 166). Corrosion-proof suit (EN 14605). Large spills/in enclosed spaces: self-contained breathing apparatus (EN 136 + EN 137). Large spills/in enclosed spaces: gas-tight suit (EN 943). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No naked flames. Large spills/in confined spaces: consider evacuation. Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation. Exposure to fire/heat: have neighbourhood close doors and windows.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Face shield (EN 166). Corrosion-proof suit (EN 14605). Large spills/in enclosed spaces: self-contained breathing apparatus (EN 136 + EN 137). Large spills/in enclosed spaces: gas-tight suit (EN 943).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product, collect/pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers.

Damaged/cooled tanks must be emptied. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately. Keep container tightly closed. Do not discharge the waste into the drain.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Meet the legal requirements. Provide for a tub to collect spills.

7.2.2 Keep away from:

Heat sources.

7.2.3 Suitable packaging material:

No data available

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

3 / 18

Poxy Primer B

7.2.4 Non suitable packaging material:
No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Belgium

m-Xylène α , α' -diamine	Short time value	0.1 mg/m ³ (1)
--	------------------	---------------------------

(1) M: La mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage.

France

m-Xylène- α , α' -diamine	Short time value (VL: Valeur non réglementaire indicative)	0.1 mg/m ³
---	--	-----------------------

Germany

Benzylalkohol	Time-weighted average exposure limit 8 h (TRGS 900)	22 mg/m ³ (1)
	Time-weighted average exposure limit 8 h (TRGS 900)	5 ppm (1)
	<i>Summe aus Dampf und Aerosolen.</i>	
m-Xylylendiamin	<i>Der Stoff kann gleichzeitig als Dampf und Aerosol vorliegen.</i>	

(1) UF: 2 (I)

Austria

α , α' -Diamino-1,3-xylol	Tagesmittelwert (MAK)	0.1 mg/m ³
	Kurzzeitwert Mow (MAK)	

USA (TLV-ACGIH)

m-Xylene alfa,alfa'-diamine	Momentary value (TLV - Adopted Value)	0.018 ppm
-----------------------------	---------------------------------------	-----------

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

Product name	Test	Number
Amines, aromatic	NIOSH	2002
Benzyl Alcohol	OSHA	2009
Butyl Acrylate	OSHA	2011
m-Xylene-a,a-diamine	OSHA	105

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

3-butoxypropan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	147 mg/m ³	
	Long-term systemic effects dermal	52 mg/kg bw/day	
	Long-term local effects dermal	50 %	
	Acute local effects dermal	50 %	

benzyl alcohol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	22 mg/m ³	
	Acute systemic effects inhalation	110 mg/m ³	
	Long-term systemic effects dermal	8 mg/kg bw/day	
	Acute systemic effects dermal	40 mg/kg bw/day	

m-phenylenebis(methylamine)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1.2 mg/m ³	
	Long-term local effects inhalation	0.2 mg/m ³	
	Long-term systemic effects dermal	0.33 mg/kg bw/day	

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	0.705 mg/m ³	
	Long-term systemic effects dermal	0.28 mg/kg bw/day	

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

4 / 18

Poxy Primer B

DNEL/DMEL - General population

3-butoxypropan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	43 mg/m ³	
	Long-term systemic effects dermal	22 mg/kg bw/day	
	Long-term local effects dermal	50 %	
	Acute local effects dermal	50 %	
	Long-term systemic effects oral	12.5 mg/kg bw/day	

benzyl alcohol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	5.4 mg/m ³	
	Acute systemic effects inhalation	27 mg/m ³	
	Long-term systemic effects dermal	4 mg/kg bw/day	
	Acute systemic effects dermal	20 mg/kg bw/day	
	Long-term systemic effects oral	4 mg/kg bw/day	
	Acute systemic effects oral	20 mg/kg bw/day	

PNEC

3-butoxypropan-2-ol

Compartments	Value	Remark
Fresh water	0.525 mg/l	
Marine water	0.052 mg/l	
Fresh water (intermittent releases)	5.25 mg/l	
STP	10 mg/l	
Fresh water sediment	2.36 mg/kg sediment dw	
Marine water sediment	0.236 mg/kg sediment dw	
Soil	0.16 mg/kg soil dw	

benzyl alcohol

Compartments	Value	Remark
Fresh water	1 mg/l	
Marine water	0.1 mg/l	
Fresh water (intermittent releases)	2.3 mg/l	
STP	39 mg/l	
Fresh water sediment	5.27 mg/kg sediment dw	
Marine water sediment	0.527 mg/kg sediment dw	
Soil	0.456 mg/kg soil dw	

m-phenylenebis(methylamine)

Compartments	Value	Remark
Fresh water	0.094 mg/l	
Fresh water (intermittent releases)	0.152 mg/l	
Marine water	0.009 mg/l	
STP	10 mg/l	
Fresh water sediment	12.4 mg/kg sediment dw	
Marine water sediment	1.24 mg/kg sediment dw	
Soil	2.44 mg/kg soil dw	

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Compartments	Value	Remark
Fresh water	< 0.01 mg/l	
Marine water	< 0.01 mg/l	
Fresh water (intermittent releases)	0.002 mg/l	
Marine water (intermittent releases)	0.002 mg/l	
STP	1 mg/l	
Fresh water sediment	0.002 mg/kg sediment dw	
Marine water sediment	< 0.001 mg/kg sediment dw	
Soil	< 0.001 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

5 / 18

Poxy Primer B

Protective gloves against chemicals (EN 374).

c) Eye protection:

Face shield (EN 166).

d) Skin protection:

Corrosion-proof clothing (EN 14605).

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Liquid
Colour	No data available on colour
Odour	No data available on odour
Odour threshold	No data available (test not performed)
Melting point	No data available (test not performed)
Boiling point	No data available (test not performed)
Flammability	Not classified as flammable
Explosion limits	No data available (test not performed)
Flash point	No data available (test not performed)
Auto-ignition temperature	No data available (test not performed)
Decomposition temperature	No data available (test not performed)
pH	No data available (test not performed)
Kinematic viscosity	No data available (test not performed)
Dynamic viscosity	No data available (test not performed)
Solubility	No data available (test not performed)
Log Kow	Not applicable (mixture)
Vapour pressure	No data available (test not performed)
Absolute density	1034 kg/m ³
Relative density	1.03
Relative vapour density	No data available (test not performed)
Particle size	Not applicable (liquid)

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Heating increases the fire hazard.

10.2. Chemical stability

No data available.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

Poxy Primer B

No (test) data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

6 / 18

Poxy Primer B

3-butoxypropan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	3300 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	OECD 402	> 2000 mg/kg bw	24 h	Rat (male / female)	Experimental value	
Inhalation (vapours)	LC0	Equivalent to OECD 403	> 651 ppm	4 h	Rat (male / female)	Experimental value	

benzyl alcohol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		1620 mg/kg bw		Rat (male)	Experimental value	
Dermal	LD50	EPA OTS 798.1100	> 2000 mg/kg	24 h	Rabbit (male / female)	Experimental value	
Inhalation (aerosol)	LC50	OECD 403	> 4.18 mg/l air	4 h	Rat (male / female)	Experimental value	

m-phenylenebis(methylamine)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	930 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50		> 3100 mg/kg bw	24 h	Rat (male / female)	Experimental value	
Inhalation (aerosol)	LC50	OECD 403	1.34 mg/l	4 h	Rat (male / female)	Experimental value	

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 10000 mg/kg bw		Rabbit (male / female)	Experimental value	
Oral			category 4			Literature study	
Dermal						Data waiving	
Inhalation						Data waiving	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

Poxy Primer B

No (test) data on the mixture available

Classification is based on the relevant ingredients

3-butoxypropan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Skin	Irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

benzyl alcohol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405	24 h	24; 48; 72 hours	Rabbit	Experimental value	Single treatment with rinsing
Skin	Slightly irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

m-phenylenebis(methylamine)

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye						Data waiving	
Eye	Serious eye damage; category 1					Experimental value	
Skin	Corrosive	Equivalent to EU Method B.4	4 h	4 hours	Rat	Experimental value	

Data waiving for eye corrosion based on corrosive properties

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

7 / 18

Poxy Primer B

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Serious eye damage	OECD 437	240 minutes		Bovine eye (in vitro)	Experimental value	
Not applicable (in vitro test)	Corrosive	OECD 431	3 minutes - 60 minutes		Reconstructed human epidermis	Experimental value	

Conclusion

Causes severe skin burns and eye damage.

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

Poxy Primer B

No (test) data on the mixture available

Classification is based on the relevant ingredients

3-butoxypropan-2-ol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig	Experimental value	

benzyl alcohol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal (on the ears)	Not sensitizing	OECD 429			Mouse (female)	Experimental value	

m-phenylenebis(methylamine)

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal (on the ears)	Sensitizing	OECD 429			Mouse (female)	Experimental value	

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal (on the ears)	Sensitizing	OECD 429			Mouse (female)	Experimental value	

Conclusion

May cause an allergic skin reaction.

Not classified as sensitizing for inhalation

Specific target organ toxicity

Poxy Primer B

No (test) data on the mixture available

Judgement is based on the relevant ingredients

3-butoxypropan-2-ol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (drinking water)	NOAEL	OECD 408	350 mg/kg bw/day	Liver; kidney (no effect)	13 weeks (daily)	Rat (male / female)		
Dermal	NOAEL	OECD 411	880 mg/kg bw/day	No effect	13 weeks (5 days / week)	Rat (male / female)	Experimental value	
Inhalation	NOAEL	OECD 412	> 700 ppm	No effect	2 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

benzyl alcohol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	Equivalent to OECD 451	400 mg/kg bw/day	No effect	103 weeks (5 days / week)	Rat (male / female)	Experimental value	
Dermal							Data waiving	
Inhalation (aerosol)	NOAEC	OECD 412	1072 mg/m ³	No effect	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

m-phenylenebis(methylamine)

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOEL	Equivalent to OECD 407	150 mg/kg bw/day	No effect	4 weeks (daily)	Rat (male / female)	Experimental value	
Dermal							Data waiving	
Inhalation (aerosol)	NOAEC	OECD 413	5 mg/m ³ air	No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

8 / 18

Poxy Primer B

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	OECD 422	60 mg/kg bw/day	No adverse systemic effects		Rat (male / female)	Experimental value	

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

Poxy Primer B

No (test) data on the mixture available

Judgement is based on the relevant ingredients

3-butoxypropan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

benzyl alcohol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	
Positive without metabolic activation, negative with metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)		Experimental value	

m-phenylenebis(methylamine)

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	
Negative without metabolic activation	OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S. typhimurium and E. coli)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value	

Mutagenicity (in vivo)

Poxy Primer B

No (test) data on the mixture available

Judgement is based on the relevant ingredients

benzyl alcohol

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male)	Bone marrow (no effect)	Experimental value	Single intraperitoneal injection

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

9 / 18

Poxy Primer B

m-phenylenebis(methylamine)

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Oral (stomach tube))	OECD 474		Mouse (male / female)	Bone marrow (no effect)	Experimental value	Single treatment

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

Poxy Primer B

No (test) data on the mixture available

Judgement is based on the relevant ingredients

3-butoxypropan-2-ol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)	NOEL	OECD 453	3000 ppm	No carcinogenic effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	

benzyl alcohol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	Dose level	Equivalent to OECD 451	400 mg/kg bw/day	No carcinogenic effect	1003 weeks (5 days / week)	Rat (male / female)	Experimental value	

m-phenylenebis(methylamine)

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Unknown							Data waiving	

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

Poxy Primer B

No (test) data on the mixture available

Judgement is based on the relevant ingredients

3-butoxypropan-2-ol

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Dermal)	NOAEL	OECD 414	880 mg/kg bw/day	11 day(s)	Rat	No effect	Experimental value	
Maternal toxicity (Dermal)	NOAEL	OECD 414	880 mg/kg bw/day	11 day(s)	Rat	No effect	Experimental value	
Effects on fertility (Inhalation (vapours))	NOAEL	OECD 416	300 ppm		Rat (male / female)	No effect	Read-across	

benzyl alcohol

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEL	Developmental toxicity study	175 mg/kg bw/day	10 days (1x / day)	Rat	No effect	Read-across	
Maternal toxicity (Oral (stomach tube))	NOAEL	Developmental toxicity study	175 mg/kg bw/day	10 days (1x / day)	Rat	No effect	Read-across	
Effects on fertility (Oral (diet))	NOAEL		≥ 750 mg/kg bw/day		Rat (male / female)	No effect	Read-across	

m-phenylenebis(methylamine)

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEL	OECD 414	300 mg/kg bw/day	14 day(s)	Rat	No effect	Experimental value	
Maternal toxicity (Oral (stomach tube))	NOAEL	OECD 414	100 mg/kg bw/day	14 day(s)	Rat	No effect	Experimental value	
Effects on fertility (Oral (stomach tube))	NOEL	OECD 421	50 mg/kg bw/day		Rat (male)	Male reproductive organ (no effect)	Experimental value	
Effects on fertility (Oral (stomach tube))	NOEL	OECD 421	150 mg/kg bw/day		Rat (female)	Female reproductive organ (no effect)	Experimental value	

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

10 / 18

Poxy Primer B

reaction products of ethylenediamine and 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)]bisoxirane

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Effects on fertility (Oral (stomach tube))	NOEL	OECD 422	60 mg/kg bw/day		Rat (male / female)	No effect	Experimental value	

Conclusion

Not classified for reprotoxic or developmental toxicity

Aspiration hazard

Poxy Primer B

Judgement is based on the relevant ingredients
Not classified for aspiration toxicity

Toxicity other effects

Poxy Primer B

No (test) data on the mixture available

Chronic effects from short and long-term exposure

Poxy Primer B

Skin rash/inflammation.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

Poxy Primer B

No (test) data on the mixture available

Classification is based on the relevant ingredients

3-butoxypropan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	560 mg/l - 1000 mg/l	96 h	Poecilia reticulata	Static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EC50	OECD 202	> 1000 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	Equivalent to OECD 201	> 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Toxicity aquatic micro-organisms	EC50	OECD 209	> 1000 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; Nominal concentration

benzyl alcohol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		460 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	230 mg/l	48 h	Daphnia magna		Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	NOEC	OECD 201	310 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
	ErC50	OECD 201	770 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEC	ECOSAR v1.00	48.897 mg/l	30 day(s)	Pisces		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOEC	OECD 211	51 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP
Toxicity aquatic micro-organisms	IC50	ISO 8192	2100 mg/l	49 h	Activated sludge	Static system	Fresh water	Experimental value
	IC50	ISO 8192	390 mg/l	24 h	Nitrosomonas	Static system	Fresh water	Experimental value; Inhibition

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

11 / 18

Poxy Primer B

m-phenylenebis(methylamine)

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	87.6 mg/l	96 h	Oryzias latipes	Semi-static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	15.2 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	33.3 mg/l	72 h	Pseudokirchneriella subcapitata	Static system		Experimental value; Nominal concentration
	NOEC	OECD 201	22.9 mg/l	72 h	Pseudokirchneriella subcapitata	Static system		Experimental value; Growth rate
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea	NOEC	OECD 211	4.7 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	EC50	OECD 209	> 1000 mg/l	30 minutes	Activated sludge	Static system		Experimental value; Respiration

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Toxicity algae and other aquatic plants	EL50	OECD 201	0.16 mg/l	72 h	Pseudokirchneriella subcapitata	Semi-static system	Fresh water	Experimental value; Cell numbers
	NOELR	OECD 201	0.1 mg/l	72 h	Pseudokirchneriella subcapitata	Semi-static system	Fresh water	Experimental value; Growth rate

Conclusion

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

3-butoxypropan-2-ol

Biodegradation water

Method	Value	Duration	Value determination
OECD 301E	90 %; GLP	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	4.6 h	1.5E6 /cm ³	Calculated value

benzyl alcohol

Biodegradation water

Method	Value	Duration	Value determination
Equivalent to OECD 301C	92 % - 96 %; Oxygen consumption	14 day(s)	Experimental value

m-phenylenebis(methylamine)

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	49 %; Carbon dioxide	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	1.797 h	1.5E6 /cm ³	Calculated value

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	0 %; GLP	28 day(s)	Experimental value

Conclusion

Water

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

Poxy Primer B

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

3-butoxypropan-2-ol

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		1.2	20 °C	Experimental value

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

12 / 18

Poxy Primer B

benzyl alcohol

Log Kow

Method	Remark	Value	Temperature	Value determination
		1.05	20 °C	Experimental value

m-phenylenebis(methylamine)

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 107		0.18	25 °C	Experimental value

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Log Kow

Method	Remark	Value	Temperature	Value determination
		2	20 °C	Experimental value

Conclusion

No straightforward conclusion can be drawn based upon the available numerical values

12.4. Mobility in soil

3-butoxypropan-2-ol

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.64 - 0.97	Calculated value

benzyl alcohol

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	1.122 - 1.332	Calculated value

m-phenylenebis(methylamine)

(log) Koc

Parameter	Method	Value	Value determination
log Koc		3.11	QSAR

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	1.2	QSAR

Conclusion

Contains component(s) with potential for mobility in the soil

Contains component(s) that adsorb(s) into the soil

12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

Poxy Primer B

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

3-butoxypropan-2-ol

Groundwater

Groundwater pollutant

m-phenylenebis(methylamine)

Water ecotoxicity pH

pH shift

reaction products of ethylenediamine and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Water ecotoxicity pH

pH shift

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

13 / 18

Poxy Primer B

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point. Contains no organic halogen which may add to the AOX value.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

UN number	1760
-----------	------

14.2. UN proper shipping name

Proper shipping name	corrosive liquid, n.o.s. (reaction products of ethylenediamine and 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)] bisoxirane)
----------------------	--

14.3. Transport hazard class(es)

Hazard identification number	80
Class	8
Classification code	C9

14.4. Packing group

Packing group	III
Labels	8

14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

14.6. Special precautions for user

Special provisions	274
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Rail (RID)

14.1. UN number

UN number	1760
-----------	------

14.2. UN proper shipping name

Proper shipping name	corrosive liquid, n.o.s. (reaction products of ethylenediamine and 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)] bisoxirane)
----------------------	--

14.3. Transport hazard class(es)

Hazard identification number	80
Class	8
Classification code	C9

14.4. Packing group

Packing group	III
Labels	8

14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

14.6. Special precautions for user

Special provisions	274
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Inland waterways (ADN)

14.1. UN number/ID number

UN number/ID number	1760
---------------------	------

14.2. UN proper shipping name

Proper shipping name	corrosive liquid, n.o.s. (reaction products of ethylenediamine and 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)] bisoxirane)
----------------------	--

14.3. Transport hazard class(es)

Class	8
Classification code	C9

14.4. Packing group

Packing group	III
---------------	-----

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

14 / 18

Poxy Primer B

Labels	8
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	274
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1760
14.2. UN proper shipping name	
Proper shipping name	corrosive liquid, n.o.s. (reaction products of ethylenediamine and 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)] bisoxirane)
14.3. Transport hazard class(es)	
Class	8
14.4. Packing group	
Packing group	III
Labels	8
14.5. Environmental hazards	
Marine pollutant	P
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	223
Special provisions	274
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable, based on available data

Air (ICAO-TI/IATA-DGR)

14.1. UN number/ID number	
UN number/ID number	1760
14.2. UN proper shipping name	
Proper shipping name	corrosive liquid, n.o.s. (reaction products of ethylenediamine and 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)] bisoxirane)
14.3. Transport hazard class(es)	
Class	8
14.4. Packing group	
Packing group	III
Labels	8
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A3
Special provisions	A803
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	1 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
< 50 %	
< 517 g/l	

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
E1 Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100	200	None	Eco-toxicity

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

15 / 18

Poxy Primer B

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
<ul style="list-style-type: none"> · 3-butoxypropan-2-ol · benzyl alcohol · formaldehyde, polymer with m-phenylenebis(methylamine) and phenol · m-phenylenebis(methylamine) 	<p>Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:</p> <p>(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;</p> <p>(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;</p> <p>(c) hazard class 4.1;</p> <p>(d) hazard class 5.1.</p>	<ol style="list-style-type: none"> 1. Shall not be used in: <ul style="list-style-type: none"> — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: <ul style="list-style-type: none"> — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: <ol style="list-style-type: none"> a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
<ul style="list-style-type: none"> · 3-butoxypropan-2-ol 	<p>Substances falling within one or more of the following points:</p> <p>(a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008:</p> <ul style="list-style-type: none"> — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 <p>(b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council</p> <p>(c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex.</p> <p>The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.</p>	<p>Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081</p>

National legislation Belgium

Poxy Primer B

No data available

m-phenylenebis(methylamine)

Résorption peau	m-Xylène α , α' -diamine; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air.
-----------------	---

National legislation The Netherlands

Poxy Primer B

Waterbezwaarlijkheid	A (1); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

National legislation France

Poxy Primer B

No data available

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

16 / 18

Poxy Primer B

National legislation Germany

Poxy Primer B

Lagerklasse (TRGS510)	8 A: Brennbare ätzende Gefahrstoffe
WGK	3; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017

3-butoxypropan-2-ol

TA-Luft	5.2.5
---------	-------

benzyl alcohol

TA-Luft	5.2.5/I
TRGS900 - Risiko der Fruchtschädigung	Benzylalkohol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Hautresorptive Stoffe	Benzylalkohol; H; Hautresorptiv

m-phenylenebis(methylamine)

TA-Luft	5.2.5/I
---------	---------

reaction products of ethylenediamine and 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)]bisoxirane

TA-Luft	5.2.1
---------	-------

National legislation Austria

Poxy Primer B

No data available

National legislation United Kingdom

Poxy Primer B

No data available

Other relevant data

Poxy Primer B

No data available

m-phenylenebis(methylamine)

TLV - Skin absorption	m-Xylene alfa,alfa'-diamine; Skin; Danger of cutaneous absorption
-----------------------	---

15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
LC0	Lethal Concentration 0 %
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

17 / 18

Poxy Primer B

according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 8

Publication date: 2023-08-23

Date of revision: 2023-11-28

Revision number: 0001

BIG number: 69331

18 / 18