SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



PREPARE & FINISH

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : PRFPARF & FINISH **Registration number REACH** : Not applicable (mixture)

Product type REACH : Special container containing a substance/mixture : The information refers to the substance/mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

TEC7*

Industrielaan 5B B-2250 Olen

2 +32 14 85 97 37

山 +32 14 85 97 38

info@tec7.be

*TEC7 is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

3 +32 14 85 97 37

4 +32 14 85 97 38

info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

Ireland - Beaumont Hospital, Dublin (NPIC):

+353 1 809 21 66 (Public 8 am- 10 pm)

+353 1 809 25 66 (Professionals)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (FC) No 1272/2008

classified as dangerous according to the criteria of Regulation (LC) No 1272/2000			
Class	Category	Hazard statements	
Aerosol	category 3	H229: Pressurised container: May burst if heated.	

2.2. Label elements

Hazard pictograms

No pictogram is used

Signal word

H-statements

Pressurised container: May burst if heated. H229

P-statements

Keep out of reach of children. P102

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Do not pierce or burn, even after use. P251

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F. P410 + P412

2.3. Other hazards

Caution! Substance is absorbed through the skin

Technische Schoolstraat 43 A, B-2440 Geel

© BIG vzw

Reason for revision: NPIC

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG) Publication date: 2021-03-24 http://www.big.be

Date of revision: 2025-10-01

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
2-butoxyethanol 01-2119475108-36	111-76-2 203-905-0	C≤7%	Acute Tox. 3; H331 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319	(1)(2)(10)	Constituent	ATE inhalation (vapour): 3 mg/l ATE oral: 1200 mg/kg
propan-2-ol 01-2119457558-25	67-63-0 200-661-7	C≤4%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent	
nitrogen	7727-37-9 231-783-9	C≤2%	Press. Gas - Compressed gas; H280	(1)(I)	Propellant is not released	

- (1) For H- and EUH-statements in full: see section 16
- (2) Substance with a Community workplace exposure limit
- (10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006
- (I) Exempted from registration under REACH according to Annex IV (Regulation (EC) No 1907/2006)

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

If you feel unwell, consult a doctor/medical service.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water.

After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

No effects known.

After skin contact:

No effects known.

After eye contact:

No effects known.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.

Major fire: Class B foam (alcohol-resistant), Water spray if puddle cannot expand.

5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.

Major fire: Water; risk of puddle expansion.

5.2. Special hazards arising from the substance or mixture

 $\label{thm:combustion:combustio$

Reason for revision: NPIC Publication date: 2021-03-24
Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 2 / 17

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No naked flames. Exposure to fire/heat: keep upwind. Exposure to fire/heat: have neighbourhood close doors and windows.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop solid spill into closing containers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Observe normal hygiene standards. Keep container tightly closed.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Store in a dry area. Keep container in a well-ventilated place. Fireproof storeroom. Keep out of direct sunlight. Protect against frost. Keep container tightly closed.

Heat sources, oxidizing agents, reducing agents, (strong) acids, (strong) bases.

7.2.3 Suitable packaging material:

No data available

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

2-Butoxyethanol	Time-weighted average exposure limit 8 h (Indicative occupational	20 ppm
	exposure limit value)	
	Time-weighted average exposure limit 8 h (Indicative occupational	98 mg/m³
	exposure limit value)	
	Short time value (Indicative occupational exposure limit value)	50 ppm
	Short time value (Indicative occupational exposure limit value)	246 mg/m³

Reason for revision: NPIC Publication date: 2021-03-24 Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 3 / 17

Belgium		,
2-Butoxyéthanol	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	98 mg/m³
	Short time value	50 ppm
	Short time value	246 mg/m ³
Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m ³
	Short time value	400 ppm
	Short time value	1000 mg/m ³
The Netherlands		
2-Butoxyethanol	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	20.4 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	100 mg/m ³
	Short time value (Public occupational exposure limit value)	50 ppm
	Short time value (Public occupational exposure limit value)	246 mg/m ³
France		
2-Butoxyéthanol	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	10 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	49 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	50 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	246 mg/m ³
Alcool isopropylique	Short time value (VL: Valeur non réglementaire indicative)	400 ppm
	Short time value (VL: Valeur non réglementaire indicative)	980 mg/m ³
Germany		
2-Butoxyethanol	Time-weighted average exposure limit 8 h (TRGS 900)	10 ppm (1)
	Time-weighted average exposure limit 8 h (TRGS 900)	49 mg/m ³ (1)
Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm (2)
	Time-weighted average exposure limit 8 h (TRGS 900)	500 mg/m³ (2
1) UF: 2 (I) 2) UF: 2 (II)		
Austria 2-Butoxyethanol	Tagesmittelwert (MAK)	20 ppm
E Butoxyethanor	Tagesmittelwert (MAK)	98 mg/m ³
	Kurzzeitwert 30(Miw) 4x (MAK)	40 ppm
		200 mg/m ³
2-Propanol	Kurzzeitwert 30(Miw) 4x (MAK)	200 mg/m² 200 ppm
<u> τι οματίσι</u>	Tagesmittelwert (MAK)	500 mg/m ³
	Tagesmittelwert (MAK)	<u> </u>
	Kurzzeitwert 15(Miw) 4x (MAK)	800 ppm 2000 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	Leggo Hig/III.
UK 2-Butoxyethanol	Time unighted average over source limit 9 h (Westerlage average limit)	25 nnm
z-butoxyetilalioi	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	25 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	123 mg/m³
	Short time value (Workplace exposure limit (EH40/2005))	50 ppm
2 1	Short time value (Workplace exposure limit (EH40/2005))	246 mg/m³
Propan-2-ol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	999 mg/m³
	(=	
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm 1250 mg/m ³

Reason for revision: NPIC Publication date: 2021-03-24

Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 4 / 17

Ireland

2-Butoxyethanol	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	20 ppm
	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values) Short time value (Binding occupational exposure limit values)	
	Short time value (Binding occupational exposure limit values)	246 mg/m ³
Isopropyl alcohol	Time-weighted average exposure limit 8 h (Advisory occupational exposure limit values)	200 ppm
	Short time value (Advisory occupational exposure limit values)	400 ppm

USA (TLV-ACGIH)

2-Butoxyethanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	20 ppm
2-propanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	400 ppm

b) National biological limit values

If limit values are applicable and available these will be listed below.

Germany

2-Butoxyethanol (Butoxyessigsäure	Urin: am schichtende, bei langzeitexposition nach	150 mg/g	
(nach Hydrolyse))	mehreren vorangegangenen schichten	Kreatinin	
Propan-2-ol (Aceton)	Urin: expositionsende, bzw. schichtende	25 mg/l	
Propan-2-ol (Aceton)	Vollblut: expositionsende, bzw. schichtende	25 mg/l	

UK

2-Butoxyethanol (butoxyacetic acid)	Urine: post shift	240 mmol/mol	
		creatinine	

USA (BEI-ACGIH)

2-buthoxyethanol (Butoxyacetic acid (BAA))		200 mg/g creatinine	With hydrolysis
2-Propanol (Acetone)	Urine: end of shift at end of workweek	40 mg/L	Background, Nonspecific

8.1.2 Sampling methods

Product name	Test	Number
2-Butoxyethanol (Alcohols IV)	NIOSH	1403
2-Butoxyethanol (Butyl Cellosolve solvent)	OSHA	83
2-Butoxyethanol	OSHA	5001
Butoxyacetic acid	NIOSH	8316
Butyl cellosolve (Volatile Organic compounds)	NIOSH	2549
Butyl Cellosolve	OSHA	83
Isopropanol (Volatile Organic compounds)	NIOSH	2549
Isopropyl Alcohol (Alcohols I)	NIOSH	1400
Isopropyl Alcohol	NIOSH	3900
Isopropyl Alcohol	OSHA	5001

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

<u>DNEL/DMEL - Workers</u> 2-butoxyethanol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	98 mg/m³	
	Acute systemic effects inhalation	1091 mg/m³	
	Acute local effects inhalation	246 mg/m³	

propan-2-ol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m³	
	Acute systemic effects inhalation	1000 mg/m³	
	Long-term systemic effects dermal	888 mg/kg bw/day	

DNEL/DMEL - General population 2-butoxyethanol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	59 mg/m³	
	Acute systemic effects inhalation	426 mg/m³	
	Acute local effects inhalation	147 mg/m³	
	Long-term systemic effects oral	6.3 mg/kg bw/day	
	Acute systemic effects oral	26.7 mg/kg bw/day	

Reason for revision: NPIC Publication date: 2021-03-24

Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 5 / 17

propan-2-ol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m³	
	Acute systemic effects inhalation	178 mg/m³	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	
	Acute systemic effects oral	51 mg/kg bw/day	

PNEC

2-butoxyethanol

Compartments	Value	Remark
Fresh water	8.8 mg/l	
Marine water	0.88 mg/l	
Fresh water (intermittent releases)	26.4 mg/l	
STP	463 mg/l	
Fresh water sediment	34.6 mg/kg sediment dw	
Marine water sediment	3.46 mg/kg sediment dw	
Soil	2.33 mg/kg soil dw	
Oral	0.02 g/kg food	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Respiratory protection not required in normal conditions.

b) Hand protection:

Protective gloves against chemicals (EN 374).

	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

c) Eye protection:

Eye protection not required in normal conditions.

d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Press-pack					
	Liquid					
Colour	No data available on colour					
Odour	Characteristic odour					
Odour threshold	No data available in the literature					
Melting point	<0 °C					
Boiling point	82 °C - 173 °C					
Flammability	Not classified as flammable					
Explosion limits	1.13 - 12 vol %					
Flash point	> 58 °C					
Auto-ignition temperature	230 °C					
Decomposition temperature	No data available in the literature					
рН	7					
Kinematic viscosity	No data available in the literature					
Dynamic viscosity	1 mPa.s ; 20 °C					
Solubility	Water; complete					
Log Kow	Not applicable (mixture)					
Vapour pressure	No data available in the literature					
Absolute density	995 kg/m³ ; 20 °C					
Relative density	1.00 ; 20 °C					
Relative vapour density	No data available in the literature					
Particle size	Not applicable (liquid)					

9.2. Other information

Reason for revision: NPIC Publication date: 2021-03-24

Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 6 / 17

Evaporation rate 1.3; Butyl acetate

SECTION 10: Stability and reactivity

10.1. Reactivity

Heating increases the fire hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Keep away from naked flames/heat.

10.5. Incompatible materials

Oxidizing agents, reducing agents, (strong) acids, (strong) bases.

10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

PREPARE & FINISH

No (test)data on the mixture available

Judgement is based on the relevant ingredients

2-butoxyethanol

Route of exposure	Parameter	Method	Value	Exposure time			Remark
						determination	
Oral	ATE		1200 mg/kg bw			Annex VI	
Oral	LD50	Equivalent to OECD 401	1746 mg/kg bw		Rat (male)	Experimental value	
Oral	LD50	OECD 401	1414 mg/kg bw		Guinea pig (male / female)	Experimental value	
Dermal	LC0	OECD 402	> 2000 mg/kg bw	24 h	Guinea pig (male / female)	Experimental value	
Inhalation (vapours)	ATE		3 mg/l			Annex VI	
Inhalation (saturated vapour)	Dose level	Equivalent to OECD 433	2.25 mg/l	4 h	Guinea pig (male / female)	Experimental value	No effect

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	'	13120 mg/kg bw/day	24 h	Rabbit	Experimental value	Converted value
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	-	Rat (male / female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

PREPARE & FINISH

No (test)data on the mixture available

Judgement is based on the relevant ingredients

2-butoxyethanol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye	Irritating	OECD 405	24 h	24; 48; 72 hours	Rabbit	'	Single treatment with rinsing
Skin	Irritating	EU Method B.4	4 h	24; 48; 72 hours	Rabbit	Experimental value	

Reason for revision: NPIC Publication date: 2021-03-24
Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 7 / 17

propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	 Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		1; 2; 3; 4; 7; 10; 14 days	'	Single treatment without rinsing
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Experimental value	

Conclusion

Not classified as irritating to the respiratory system

Not classified as irritating to the skin

Not classified as irritating to the eyes

Respiratory or skin sensitisation

PREPARE & FINISH

No (test)data on the mixture available

Judgement is based on the relevant ingredients

2-butoxyethanol

Route of exposure	Result	Method	•	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

propan-2-ol

Route of exposure	Result	Method	•	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

Conclusion

Not classified as sensitizing for inhalation

Not classified as sensitizing for skin $\,$

Specific target organ toxicity

PREPARE & FINISH

No (test)data on the mixture available

Judgement is based on the relevant ingredients

2-butoxyethanol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time		Value determination	Remark
Oral (drinking water)	NOAEL	Equivalent to OECD 408	< 69 mg/kg bw/day	No effect	90 days (continuous)	Rat (male)	Experimental value	
Oral (drinking water)	NOAEL	Equivalent to OECD 408	< 82 mg/kg bw/day	No effect	90 day(s)	Rat (female)	Experimental value	
Dermal	NOAEL	Equivalent to OECD 411	> 150 mg/kg bw/day	No effect	(/ -	Rabbit (male / female)	Experimental value	
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	< 31 ppm	No effect	14 weeks (6h / day, 5 days / week)	Rat (female)	Experimental value	
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	62.5 ppm	No effect	14 weeks (6h / day, 5 days / week)	Rat (male)	Experimental value	

propan-2-ol

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral							Data waiving	
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm	No adverse systemic effects	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	
Inhalation (vapours)	Dose level	Equivalent to OECD 403	5000 ppm	Central nervous system (drowsiness, dizziness)	6 h	Rat (male / female)	Experimental value	

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

PREPARE & FINISH

No (test)data on the mixture available Judgement is based on the relevant ingredients

Reason for revision: NPIC Publication date: 2021-03-24
Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 8 / 17

2-butoxyethanol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)		Experimental value	

propan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	

Mutagenicity (in vivo)

PREPARE & FINISH

No (test)data on the mixture available

Judgement is based on the relevant ingredients

2-butoxyethanol

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	Equivalent to OECD 474	3 dose(s)/24-hour	Mouse (male)	No effect	Experimental value	
		interval				

propan-2-ol

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male /	No effect	Experimental value	Single
			female)			intraperitoneal
						injection

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

PREPARE & FINISH

No (test)data on the mixture available

Judgement is based on the relevant ingredients

2-butoxyethanol

Route of	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
exposure								
Inhalation	NOAEC	Equivalent to	> 125 ppm	No carcinogenic	104 weeks (6h /	Rat (male /	Experimental value	
(vapours)		OECD 451		effect	day, 5 days /	female)		
					week)			

propan-2-ol

Route of	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
exposure								
Inhalation	NOEL	OECD 451	5000 ppm	No carcinogenic	104 weeks (6h /	Rat (male /	Experimental value	
(vapours)				effect	day, 5 days /	female)		
					week)			

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

PREPARE & FINISH

No (test)data on the mixture available Judgement is based on the relevant ingredients

Reason for revision: NPIC Publication date: 2021-03-24
Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 9 / 17

2-butoxyethanol

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEC	Equivalent to OECD 414	200 mg/kg bw/day	3 days (gestation, daily)	Rat	No effect	Experimental value	
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	3 days (gestation, daily)	Rat	No effect	Experimental value	
Effects on fertility (Oral (drinking water))	NOAEL	Fertility Assessment	720 mg/kg bw/day		Mouse (male / female)	No effect	Experimental value	

propan-2-ol

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value	Remark
							determination	
Developmental toxicity	NOAEL	Equivalent to	400 mg/kg	10 day(s)	Rat	Foetus (no	Experimental	
(Oral (stomach tube))		OECD 414	bw/day			effect)	value	
Maternal toxicity (Oral	NOAEL	Equivalent to	400 mg/kg	10 day(s)	Rat	No effect	Experimental	
(stomach tube))		OECD 414	bw/day				value	
Effects on fertility (Oral	NOAEL	Equivalent to	> 1000		Rat (male /	No effect	Experimental	
(stomach tube))		OECD 416	mg/kg		female)		value	
			bw/day					

Conclusion

Not classified for reprotoxic or developmental toxicity

Aspiration hazard

PREPARE & FINISH

Judgement is based on the relevant ingredients Not classified for aspiration toxicity

Toxicity other effects

PREPARE & FINISH

No (test)data on the mixture available

Chronic effects from short and long-term exposure

PREPARE & FINISH

No effects known.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

PREPARE & FINISH

No (test)data on the mixture available

Judgement of the mixture is based on the relevant ingredients

2-butoxyethanol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	1474 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	1550 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	1840 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	286 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	Equivalent to OECD 204	> 100 mg/l	21 day(s)	Danio rerio	Semi-static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity aquatic crustacea	NOEC	OECD 211	100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro- organisms	Toxicity threshold	Equivalent to DIN 38412/8	700 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Nominal concentration

Reason for revision: NPIC Publication date: 2021-03-24

Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 10 / 17

propan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	9640 mg/l - 10000 mg/l	96 h	Pimephales promelas	Flow- through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	Toxicity threshold		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Long-term toxicity fish	NOELR	Petrotox computer model	> 1000 mg/l	28 day(s)	Brachydanio rerio			Estimated value
Long-term toxicity aquatic crustacea	NOEC		141 mg/l	16 day(s)	Daphnia magna		Fresh water	Experimental value; Growth
Toxicity aquatic micro- organisms	Toxicity threshold	Equivalent to DIN 38412/8	1050 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Toxicity test
	EC50	ISO 8192	41676 mg/l	30 minutes	Activated sludge			Experimental value

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

2-butoxyethanol

Biodegradation water

Method		/alue	Duration	Value determination	
OECD 301B		00 %; Carbon dioxide	28 day(s)	Experimental value	

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.90	5.5 h	1.5E6 /cm ³	QSAR

propan-2-ol

Biodegradation water

Method	Value	Duration	Value determination
EU Method C.5	53 %; Oxygen consumption	5 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	18 h	1.5E6 /cm³	Calculated value

Conclusion

Water

The surfactant(s) is/are biodegradable according to Regulation (EC) No 648/2004

12.3. Bioaccumulative potential

PREPARE & FINISH

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

2-butoxyethanol

Log Kow

•						
Method	Remark	Value	Temperature	Value determination		
BASF test			25 °C	Experimental value		

propan-2-ol

og Kow						
Method	Remark	Value	Temperature	Value determination		
			25 °C	Weight of evidence approach		

Conclusion

Does not contain bioaccumulative component(s)

12.4. Mobility in soil

<u>2-butoxyethanol</u>

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.5 - 0.9	Calculated value

Percent distribution

Method	Fraction air		Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level I	0.31 %	0 %	0.01 %	0.59 %	99 %	QSAR

Reason for revision: NPIC Publication date: 2021-03-24
Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 11 / 17

propan-2-ol

(log) Koc

Parameter	Method	Value	Value determination
log Koc		0.19 - 0.54	Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

PREPARE & FINISH

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

2-butoxyethanol

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

propan-2-ol

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Can be considered as non hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

12 01 99 (wastes from shaping and physical and mechanical surface treatment of metals and plastics: wastes not otherwise specified). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Specific treatment. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

No data available

SECTION 14: Transport information

Road (ADR)

14.1. UN number or ID number		
UN number	1950	
14.2. UN proper shipping name		
Proper shipping name	aerosols	
14.3. Transport hazard class(es)		
Hazard identification number		
Class	2	
Classification code	5A	
14.4. Packing group		
Packing group		
Labels	2.2	
14.5. Environmental hazards		
Environmentally hazardous substance mark	no	
14.6. Special precautions for user		
Special provisions	190	

Reason for revision: NPIC Publication date: 2021-03-24
Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 12 / 17

PREP	ARE & FINISH
Special provisions	327
Special provisions	344
•	
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg (gross mass).
l (RID)	
14.1. UN number or ID number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	20
Class	2
Classification code	5A
14.4. Packing group	Jn.
Packing group	
Labels	2.2
14. <u>5. Environmental hazards</u>	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg (gross mass).
and waterways (ADN)	
14.1. UN number or ID number	
UN number/ID number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	*
Class	2
Classification code	5A
14.4. Packing group	jon.
Packing group	
	2.2
Labels	2.2
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14. <u>6. Special precautions for user</u>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).
a (IMDG/IMSBC)	
14.1. UN number or ID number	1050
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2.2
14.4. Packing group	2.2
14.4. Packing group Packing group Labels	2.2
14.4. Packing group Packing group Labels 14.5. Environmental hazards	2.2
14.4. Packing group Packing group Labels 14.5. Environmental hazards Marine pollutant	-
14.4. Packing group Packing group Labels 14.5. Environmental hazards Marine pollutant Environmentally hazardous substance mark	2.2 - no
14.4. Packing group Packing group Labels 14.5. Environmental hazards Marine pollutant Environmentally hazardous substance mark 14.6. Special precautions for user	- no
14.4. Packing group Packing group Labels 14.5. Environmental hazards Marine pollutant Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions	- no 190
14.4. Packing group Packing group Labels 14.5. Environmental hazards Marine pollutant Environmentally hazardous substance mark 14.6. Special precautions for user	- no
14.4. Packing group Packing group Labels 14.5. Environmental hazards Marine pollutant Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions Special provisions	- no 190
14.4. Packing group Packing group Labels 14.5. Environmental hazards Marine pollutant Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions Special provisions Special provisions	- no 190 277 327
14.4. Packing group Packing group Labels 14.5. Environmental hazards Marine pollutant Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions Special provisions Special provisions Special provisions Special provisions Special provisions	- no 190 277 327 344
14.4. Packing group Packing group Labels 14.5. Environmental hazards Marine pollutant Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions	- no 190 277 327 344 381
14.4. Packing group Packing group Labels 14.5. Environmental hazards Marine pollutant Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions Special provisions Special provisions Special provisions Special provisions Special provisions	- no 190 277 327 344

Reason for revision: NPIC Publication date: 2021-03-24
Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 13 / 17

Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg (gross mass).
14.7. Maritime transport in bulk according to IMO instrum	ents
Annex II of MARPOL 73/78	Not applicable
Air (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number	
UN number/ID number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols, non-flammable
14.3. Transport hazard class(es)	
Class	2.2
14.4. Packing group	<u> </u>

Labels 14.5. Environmental hazards

Packing group

2.2 Environmentally hazardous substance mark no

14.6. Special precautions for user Special provisions A145 Special provisions A167 A802 Special provisions Special provisions A98

Passenger and cargo transport

Limited quantities: maximum net quantity per packaging

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **European legislation:**

VOC content Directive 2010/75/EU

VOC content	Remark
9.8 %	
98 g/l	

30 kg G

2-butoxyethanol

Product name	Skin resorption
2-Butoxyethanol	Skin

Directive 2012/18/EU (Seveso III)

Not subject to registration according to Directive 2012/18/EU (Seveso III)

Ingredients according to Regulation (EC) No 648/2004 and amendments

<5% non-ionic surfactants, perfumes

REACH Candidate list

Does not contain component(s) included in candidate list of substances of very high concern (SVHC) for authorisation (Article 59 of Regulation (EC) No 1907/2006)

REACH Annex XIV - Authorisation

Does not contain component(s) included in Annex XIV of Regulation (EC) No 1907/2006: list of substances subject to authorisation

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· 2-butoxyethanol · propan-2-ol	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:

Reason for revision: NPIC Publication date: 2021-03-24 Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 14 / 17

		a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legib and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legit and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
propan-2-ol	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibland indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
2-butoxyethanol propan-2-ol	Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex. The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.	

National legislation Belgium

PREPARE & FINISH

No data available

2-butoxyethanol Résorption peau

titre 2)

_			
		2-Butoxyéthanol; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air.	
р	propan-2-ol		
		alcool isopropylique; VI.2.2.; Liste des procédés au cours desquels une substance ou un mélange se dégage; Procédé à	
		l'acide fort dans la fabrication d'alcool isopropylique.	
	aux agents possédant des		
	propriétés perturbant le		

National legislation The Netherlands

système endocrinien (Code du bien-être au travail, Livre VI,

Reason for revision: NPIC Publication date: 2021-03-24

Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 15 / 17

PREPARE & FINISH		
Waterbezwaarlijkheid	B (4); Algemene Beoordelingsmethodiek (ABM)	
2-butoxvethanol		

Grenzwertes nicht befürchtet zu werden

2-Butoxyethanol; H

National legislation France PREPARE & FINISH

Huidopname (wettelijk)

No data available

2-butoxyethanol

Risque de pénétration 2-Butoxyéthanol; Risque de pénétration percutanée percutanée

National legislation Germany

PREPARE & FINISH

	WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017	
2	2-butoxyethanol		
	TA-Luft	5.2.5	
	TRGS900 - Risiko der	2-Butoxyethanol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des	
	Fruchtschädigung	biologischen Grenzwertes nicht befürchtet zu werden	
	Hautresorptive Stoffe	2-Butoxyethanol; H; Hautresorptiv	
р	propan-2-ol		
	TA-Luft	5.2.5	
	TRGS900 - Risiko der	Propan-2-ol: Y: Risiko der Fruchtschädigung braucht bei Finhaltung des Arbeitsplatzgrenzwertes und des biologischen	

Fruchtschädigung **National legislation Austria**

PREPARE & FINISH

No data available

2-butoxyethanol

besondere Gefahr der	2-Butoxyethanol; H
Hautresorption	

National legislation United Kingdom

PREPARE & FINISH

No data available

2-butoxyethanol

ISkin absorption	I2-Butoxyethanol: Sk

National legislation Ireland

PREPARE & FINISH

No data available

2-butoxyethanol

Skin resorption	2-Butoxyethanol; Skin
propan-2-ol	
Skin resorption	Isopropyl alcohol; Skin

Other relevant data

PREPARE & FINISH

No data available

2-butoxyethanol TLV - Carcinogen

TLV - Carcinogen	2-Butoxyethanol; A3	
IARC - classification	3; 2-butoxyethanol	
propan-2-ol		
TLV - Carcinogen	2-propanol; A4	
IARC - classification	3; Isopropanol	

15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

H225 Highly flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

(*) INTERNAL CLASSIFICATION BY BIG

ADI Acceptable daily intake

AOEL Acceptable operator exposure level

ATE **Acute Toxicity Estimate**

Reason for revision: NPIC Publication date: 2021-03-24

Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 16 / 17

BCF **Bioconcentration Factor** BEI **Biological Exposure Indices**

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level DNEL Derived No Effect Level EC10 Effect Concentration 10 % EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

GLP **Good Laboratory Practice** LC0 Lethal Concentration 0 % LC50 Lethal Concentration 50 %

LD50 Lethal Dose 50 %

LOAEC/LOAEL Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level NOAEC/NOAEL No Observed Adverse Effect Concentration/No Observed Adverse Effect Level

NOEC/NOEL No Observed Effect Concentration/No Observed Effect Level OECD Organisation for Economic Co-operation and Development

PRT Persistent, Bioaccumulative & Toxic PNEC **Predicted No Effect Concentration** STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: NPIC Publication date: 2021-03-24 Date of revision: 2025-10-01

Revision number: 0003 BIG number: 67037 17 / 17