



Poxy Primer

SUBSTRATE STRENGTHENER / BONDING PRIMER

- ✓ Improves and strengthens weak and powdery surfaces
- ✓ Protects iron and steel against rust, fixes loose rust particles
- ✓ Bonding primer for concrete rot repairs
- ✓ Mixing ratio 1:1

Technical Info

- Composition: epoxy resin, hardener and solvent.
- Colour: transparent yellow.
- Specific weight (mixture): 1 +/- 0.1 kg/dm³.
- Adhesion:
- Good adhesion to most building materials such as wood, stone, natural stone, concrete, ...
- Bond strength to metal: 2N/mm².
- Temperature resistance: min. -30°C / max. +60°C / temporarily up to 110°C.
- Processing time: after mixing at +20°C: 30 minutes. Higher temperatures accelerate curing and lower temperatures slow down curing.
- Processing temperature: between +5°C and +30°C.
- Drying time: dust dry and can be walked on after 12 hours.
- Chemical resistance after seven days:
- Resists water, salt water, dilute acids and bases, salts, oils, fuels, urine, fertilisers and most solvents.
- Shelf life: minimum 12 months in closed packaging - store frost-free.
- Safety measures: Please consult the safety data sheet.

Packing

Poxy Primer - 1kg

631213000

Product

Characteristics

- 2-component epoxy primer
- High penetration into porous substrates
- Strengthens weak surfaces through impregnation
- Fixes powdery surfaces
- Neutralises rust
- Suitable for indoor and outdoor use

Applications

- Concrete rust repair: neutralises rust on rebar + bonding primer for Floor Fix / Wall Fix.
- Fixing of powdery surfaces for painting / bonding.
- Reinforcing weak substrates for bonding: cellular concrete, plaster, gypsum board, plasterboard, natural stone, weathered concrete, etc.
- Bonding primer for bonding on concrete, natural stone, ...
- Reinforcing façade bricks with suspended bonding under steel beams.
- Protects concrete and facade bricks against the effects of salts, manure, urine, etc.

Use

Preparation

- Minimum processing temperature: +5°C.
- Apply to a clean, completely dry surface.
- After mixing, processable for +/- 30 minutes at temperatures of +20°C. At high temperatures, the components can be cooled for a longer processing time.
- Pour the hardener (Component B, plastic bottle) completely into the resin (Component A, can), or use the measuring cup provided for a 1:1 mixing ratio.
- Mix very thoroughly until both components are completely mixed.

Processing

- After mixing, apply immediately with a brush or roller.
- On highly absorbent surfaces: apply a second coat after +/- 1 hour or longer.
- The Tec7 adhesives and sealants can be applied wet-on-wet on Poxo Primer.
- Protect from moisture and rain for 24 hours after application.
- Can be walked on and dust dry after +/- 12 hours at +20°C. Chemically resistant after 7 days at +20°C.
- Clean tools with Spray & PUR Cleaner.
- Can be painted over with most varnishes and paints.

Use

- Depending on the porosity of the substrate:
 - First coat: 150–300 ml/m².
 - Second coat: 250 ml/m².