

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



PT7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : PT7
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Primer

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

TEC7*
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@tec7.be
*TEC7 is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

| Class | Category | Hazard statements |
|-----------------|------------|--|
| Aerosol | category 1 | H222: Extremely flammable aerosol. |
| Aerosol | category 1 | H229: Pressurised container: May burst if heated. |
| Skin Irrit. | category 2 | H315: Causes skin irritation. |
| STOT SE | category 3 | H336: May cause drowsiness or dizziness. |
| Aquatic Chronic | category 2 | H411: Toxic to aquatic life with long lasting effects. |

2.2. Label elements



Contains: hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane.

Signal word Danger

H-statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

P-statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

<http://www.big.be>

© BIG vzw

Reason for revision: 3.2; 8; 9; 12

Revision number: 0400

Publication date: 2010-12-08

Date of revision: 2021-04-14

BIG number: 50486

1 / 13

878-16433-019-en

PT7

| | |
|-------------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P280 | Wear protective gloves, protective clothing and eye protection/face protection. |
| P405 | Store locked up. |
| P410 + P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F. |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulation. |

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name REACH Registration No | CAS No EC No List No | Conc. (C) | Classification according to CLP | Note | Remark | M-factors and ATE |
|--|----------------------------|-----------|--|------------|-------------|----------------------|
| hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane 01-2119475514-35 | 921-024-6 | 50%≤C<75% | Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411 | (1)(10) | Constituent | |
| reaction mass of ethylbenzene and xylene 01-2119488216-32 | 905-588-0 | 5%≤C<10% | Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Asp. Tox. 1; H304 STOT RE 2; H373 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 | (1)(10) | Constituent | |
| dimethyl ether 01-2119472128-37 | 115-10-6 204-065-8 | 25%≤C<50% | Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280 | (1)(2)(10) | Propellant | |

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Dizziness. Drowsiness.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

No effects known.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

Reason for revision: 3.2; 8; 9; 12

Publication date: 2010-12-08

Date of revision: 2021-04-14

Revision number: 0400

BIG number: 50486

2 / 13

PT7

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Do not discharge the waste into the drain.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Keep out of direct sunlight.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

| | | |
|---------------|---|------------------------|
| Dimethylether | Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value) | 1000 ppm |
| | Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value) | 1920 mg/m ³ |

Belgium

| | | |
|--------------------|--|------------------------|
| Oxyde de diméthyle | Time-weighted average exposure limit 8 h | 1000 ppm |
| | Time-weighted average exposure limit 8 h | 1920 mg/m ³ |

The Netherlands

| | | |
|---------------|---|------------------------|
| Dimethylether | Time-weighted average exposure limit 8 h (Public occupational exposure limit value) | 496 ppm |
| | Time-weighted average exposure limit 8 h (Public occupational exposure limit value) | 950 mg/m ³ |
| | Short time value (Public occupational exposure limit value) | 783 ppm |
| | Short time value (Public occupational exposure limit value) | 1500 mg/m ³ |

France

| | | |
|--------------------|---|------------------------|
| Oxyde de diméthyle | Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative) | 1000 ppm |
| | Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative) | 1920 mg/m ³ |

Germany

| | | |
|---------------|---|------------------------|
| Dimethylether | Time-weighted average exposure limit 8 h (TRGS 900) | 1000 ppm |
| | Time-weighted average exposure limit 8 h (TRGS 900) | 1900 mg/m ³ |

UK

| | | |
|----------------|---|-----------------------|
| Dimethyl ether | Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) | 400 ppm |
| | Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) | 766 mg/m ³ |
| | Short time value (Workplace exposure limit (EH40/2005)) | 500 ppm |
| | Short time value (Workplace exposure limit (EH40/2005)) | 958 mg/m ³ |

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

If applicable and available it will be listed below.

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Effect level (DNEL/DMEL) | Type | Value | Remark |
|--------------------------|---------------------------------------|------------------------|--------|
| DNEL | Long-term systemic effects inhalation | 2035 mg/m ³ | |
| | Long-term systemic effects dermal | 773 mg/kg bw/day | |

reaction mass of ethylbenzene and xylene

| Effect level (DNEL/DMEL) | Type | Value | Remark |
|--------------------------|---------------------------------------|-----------------------|--------|
| DNEL | Long-term systemic effects inhalation | 221 mg/m ³ | |
| | Acute systemic effects inhalation | 442 mg/m ³ | |
| | Long-term local effects inhalation | 221 mg/m ³ | |
| | Acute local effects inhalation | 442 mg/m ³ | |
| | Long-term systemic effects dermal | 212 mg/kg bw/day | |

DNEL/DMEL - General population

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Effect level (DNEL/DMEL) | Type | Value | Remark |
|--------------------------|---------------------------------------|-----------------------|--------|
| DNEL | Long-term systemic effects inhalation | 608 mg/m ³ | |
| | Long-term systemic effects inhalation | 699 mg/kg bw/day | |
| | Long-term systemic effects oral | 699 mg/kg bw/day | |

PT7

reaction mass of ethylbenzene and xylene

| Effect level (DNEL/DMEL) | Type | Value | Remark |
|--------------------------|---------------------------------------|------------------------|--------|
| DNEL | Long-term systemic effects inhalation | 65.3 mg/m ³ | |
| | Acute systemic effects inhalation | 260 mg/m ³ | |
| | Long-term local effects inhalation | 65.3 mg/m ³ | |
| | Acute local effects inhalation | 260 mg/m ³ | |
| | Long-term systemic effects dermal | 125 mg/kg bw/day | |
| | Long-term systemic effects oral | 12.5 mg/kg bw/day | |

PNEC

reaction mass of ethylbenzene and xylene

| Compartments | Value | Remark |
|--------------|----------|--------|
| STP | 1.3 mg/l | |

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

| Materials | Measured breakthrough time | Thickness | Protection index | Remark |
|--------------|----------------------------|-----------|------------------|--------|
| butyl rubber | > 480 minutes | 0.4 mm | Class 6 | |

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---------------------------|--|
| Physical form | Aerosol |
| Odour | Characteristic odour |
| Odour threshold | No data available in the literature |
| Colour | Variable in colour, depending on the composition |
| Particle size | Not applicable (aerosol) |
| Explosion limits | 0.6 - 26.2 vol % ; Propellant |
| Flammability | Extremely flammable aerosol. |
| Log Kow | Not applicable (mixture) |
| Dynamic viscosity | No data available in the literature |
| | Not applicable (aerosol) |
| Kinematic viscosity | No data available in the literature |
| | Not applicable (aerosol) |
| Melting point | Not applicable (aerosol) |
| Boiling point | No data available in the literature |
| Relative vapour density | No data available in the literature |
| Vapour pressure | 4000 hPa ; 20 °C ; Liquid |
| Solubility | Water ; insoluble ; Liquid |
| Relative density | 0.70 ; 20 °C ; Liquid |
| Absolute density | 700 kg/m ³ ; 20 °C ; Liquid |
| Decomposition temperature | No data available in the literature |
| Auto-ignition temperature | Not applicable (aerosol) |
| Flash point | Not applicable (aerosol) |
| pH | Not applicable (aerosol) |

9.2. Other information

No data available

PT7

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO₂ are formed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

PT7

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Route of exposure | Parameter | Method | Value | Exposure time | Species | Value determination | Remark |
|----------------------|-----------|---------------------------|----------------------------------|---------------|------------------------|---------------------|--------|
| Oral | LD50 | | > 5840 mg/kg bw | | Rat | Read-across | |
| Dermal | LD50 | | 2800 mg/kg bw - 3100 mg/kg bw | 24 h | Rat (male / female) | Read-across | |
| Inhalation (vapours) | LC50 | Equivalent to OECD 403 | > 21 mg/l | 4 h | Rat (male / female) | Experimental value | |
| Inhalation (vapours) | LC50 | | > 25.2 mg/l | 4 h | Rat (male / female) | Experimental value | |

reaction mass of ethylbenzene and xylene

| Route of exposure | Parameter | Method | Value | Exposure time | Species | Value determination | Remark |
|----------------------|-----------|--------------------------------|-----------------|---------------|---------------|---------------------|--------|
| Oral | LD50 | Equivalent to EU Method B.1 | 3523 mg/kg bw | | Rat (male) | Experimental value | |
| Oral | LD50 | Equivalent to EU Method B.1 | > 4000 mg/kg bw | | Rat (female) | Experimental value | |
| Dermal | LD50 | | > 5000 mg/kg bw | 4 h | Rabbit (male) | Weight of evidence | |
| Dermal | | | category 4 | | | Literature study | |
| Inhalation (vapours) | LC50 | Equivalent to EU Method B.2 | 29.09 mg/l | 4 h | Rat (male) | Experimental value | |
| Inhalation (vapours) | | | category 4 | | | Literature study | |

Conclusion

Not classified for acute toxicity

Corrosion/irritation

PT7

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Route of exposure | Result | Method | Exposure time | Time point | Species | Value determination | Remark |
|-------------------|----------------|---------------------------|---------------|----------------------------------|---------|-----------------------|------------------|
| Eye | Not irritating | Equivalent to OECD 405 | | 24; 48; 72 hours | Rabbit | Read-across | Single treatment |
| Skin | Irritating | OECD 404 | 4 h | 1; 24; 48; 72 hrs; 7; 14 days | Rabbit | Experimental value | |

Reason for revision: 3.2; 8; 9; 12

Publication date: 2010-12-08

Date of revision: 2021-04-14

Revision number: 0400

BIG number: 50486

6 / 13

PT7

reaction mass of ethylbenzene and xylene

| Route of exposure | Result | Method | Exposure time | Time point | Species | Value determination | Remark |
|-------------------|------------------------------|--------|---------------|------------------|---------|---------------------|--------|
| Eye | Irritating | | 72 h | 24; 48; 72 hours | Rabbit | Experimental value | |
| Skin | Irritating | | 24 h | 24; 72 hours | Rabbit | Weight of evidence | |
| Inhalation | Irritating; STOT SE cat.3 | | | | | | |

Conclusion

Causes skin irritation.
Not classified as irritating to the respiratory system
Not classified as irritating to the eyes

Respiratory or skin sensitisation

PT7

No (test)data on the mixture available
Judgement is based on the relevant ingredients
hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Route of exposure | Result | Method | Exposure time | Observation time point | Species | Value determination | Remark |
|-------------------|-----------------|------------------------|---------------|------------------------|----------------------------|---------------------|--------|
| Skin | Not sensitizing | Equivalent to OECD 406 | | 24; 48 hours | Guinea pig (male / female) | Read-across | |

reaction mass of ethylbenzene and xylene

| Route of exposure | Result | Method | Exposure time | Observation time point | Species | Value determination | Remark |
|-------------------|-----------------|------------------------|---------------|------------------------|---------|---------------------|--------|
| Skin | Not sensitizing | Equivalent to OECD 429 | | | Mouse | Experimental value | |

Conclusion

Not classified as sensitizing for skin

Specific target organ toxicity

PT7

No (test)data on the mixture available
Classification is based on the relevant ingredients
hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Route of exposure | Parameter | Method | Value | Organ | Effect | Exposure time | Species | Value determination |
|----------------------|-----------|------------------------|-----------------------------|-------|-----------|--|-----------------------|---------------------|
| Dermal | NOAEL | Equivalent to OECD 453 | 0.5 ml | | | 52 weeks (3 times / week) - 104 weeks (3 times / week) | Mouse (male / female) | Experimental value |
| Inhalation (vapours) | NOAEC | Equivalent to OECD 413 | 24300 mg/m ³ air | | No effect | 13 weeks (6h / day, 5 days / week) | Rat (male / female) | |
| Inhalation | | | STOT SE cat.3 | | | | | Literature study |

reaction mass of ethylbenzene and xylene

| Route of exposure | Parameter | Method | Value | Organ | Effect | Exposure time | Species | Value determination |
|----------------------|-----------|--------------------------|------------------------|-------|-------------|------------------------------------|--------------|---------------------|
| Oral (stomach tube) | NOAEL | Equivalent to OECD 408 | 150 mg/kg bw/day | | | 90 day(s) | Rat (female) | Experimental value |
| Oral (stomach tube) | LOAEL | Equivalent to OECD 408 | 150 mg/kg bw/day | Liver | Weight gain | 90 day(s) | Rat (male) | Experimental value |
| Inhalation (vapours) | NOAEC | Subchronic toxicity test | 3515 mg/m ³ | | No effect | 13 weeks (6h / day, 5 days / week) | Rat (male) | Experimental value |

Conclusion

May cause drowsiness or dizziness.
Not classified for subchronic toxicity

Mutagenicity (in vitro)

PT7

No (test)data on the mixture available
Judgement is based on the relevant ingredients
hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Result | Method | Test substrate | Effect | Value determination | Remark |
|---|------------------------|--------------------------|-----------|---------------------|--------|
| Negative with metabolic activation, negative without metabolic activation | Equivalent to OECD 471 | Bacteria (S.typhimurium) | No effect | Read-across | |

Reason for revision: 3.2; 8; 9; 12

Publication date: 2010-12-08

Date of revision: 2021-04-14

Revision number: 0400

BIG number: 50486

7 / 13

PT7

reaction mass of ethylbenzene and xylene

| Result | Method | Test substrate | Effect | Value determination | Remark |
|---|------------------------------|-----------------------------|--------|---------------------|--------|
| Negative with metabolic activation, negative without metabolic activation | Equivalent to EU Method B.19 | Chinese hamster ovary (CHO) | | Experimental value | |
| Negative with metabolic activation, negative without metabolic activation | Equivalent to EU Method B.10 | Chinese hamster ovary (CHO) | | Experimental value | |

Mutagenicity (in vivo)

PT7

No (test)data on the mixture available

Judgement is based on the relevant ingredients

reaction mass of ethylbenzene and xylene

| Result | Method | Exposure time | Test substrate | Organ | Value determination |
|-------------------------|------------------------|---------------|-----------------------|-------|---------------------|
| Negative (Subcutaneous) | Equivalent to OECD 478 | | Mouse (male / female) | | Experimental value |

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

PT7

No (test)data on the mixture available

Judgement is based on the relevant ingredients

reaction mass of ethylbenzene and xylene

| Route of exposure | Parameter | Method | Value | Exposure time | Species | Effect | Organ | Value determination |
|---------------------|------------|------------------------------|------------------|----------------------------|---------------------|------------------------|-------|---------------------|
| Oral (stomach tube) | Dose level | Equivalent to EU Method B.32 | 500 mg/kg bw/day | 103 weeks (3 times / week) | Rat (male / female) | No carcinogenic effect | | Experimental value |

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

PT7

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| | Parameter | Method | Value | Exposure time | Species | Effect | Organ | Value determination |
|------------------------|-----------|------------------------|-----------------------------|------------------------------------|---------------------|-----------|-------|---------------------|
| Developmental toxicity | NOAEL | Equivalent to OECD 414 | 10560 mg/m ³ air | 10 days (6h / day) | Mouse | No effect | | Read-across |
| Maternal toxicity | NOAEL | Equivalent to OECD 414 | 3168 mg/m ³ air | 10 days (6h / day) | Mouse (female) | No effect | | Read-across |
| Effects on fertility | NOAEL | Equivalent to OECD 416 | 31680 mg/m ³ air | 13 weeks (6h / day, 5 days / week) | Rat (male / female) | No effect | | Read-across |

reaction mass of ethylbenzene and xylene

| | Parameter | Method | Value | Exposure time | Species | Effect | Organ | Value determination |
|---|-----------|------------------------|----------------------------|--------------------|---------------------|------------------------------|-------|---------------------|
| Developmental toxicity (Inhalation (vapours)) | BMCL10 | Equivalent to OECD 414 | 4698 mg/m ³ air | 15 days (6h / day) | Rat | Degeneration of heart tissue | | Experimental value |
| Maternal toxicity (Inhalation (vapours)) | BMCL10 | Equivalent to OECD 414 | 887 ppm | 15 days (6h / day) | Rat | No effect | | Experimental value |
| Effects on fertility (Inhalation (vapours)) | NOAEC | | 500 ppm | | Rat (male / female) | Degeneration of heart tissue | | Experimental value |

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

PT7

No (test)data on the mixture available

Chronic effects from short and long-term exposure

PT7

No effects known.

Reason for revision: 3.2; 8; 9; 12

Publication date: 2010-12-08

Date of revision: 2021-04-14

Revision number: 0400

BIG number: 50486

8 / 13

PT7

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

PT7

No (test) data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| | Parameter | Method | Value | Duration | Species | Test design | Fresh/salt water | Value determination |
|---|-----------|----------|--------------------|-----------|---------------------------------|--------------------|------------------|---------------------------|
| Acute toxicity fishes | LL50 | OECD 203 | 11.4 mg/l | 96 h | Oncorhynchus mykiss | Semi-static system | Fresh water | Experimental value; GLP |
| Acute toxicity crustacea | EL50 | OECD 202 | 3 mg/l | 48 h | Daphnia magna | Static system | Fresh water | Experimental value; GLP |
| Toxicity algae and other aquatic plants | ErC50 | OECD 201 | 30 mg/l - 100 mg/l | 72 h | Pseudokirchneriella subcapitata | Static system | Fresh water | Experimental value; GLP |
| Long-term toxicity fish | NOELR | | 2.045 mg/l | 28 day(s) | Oncorhynchus mykiss | | Fresh water | QSAR |
| Toxicity aquatic micro-organisms | EL50 | | 35.57 mg/l | 48 h | Tetrahymena pyriformis | | Fresh water | QSAR; Continuous exposure |

Conclusion

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Biodegradation water

| Method | Value | Duration | Value determination |
|-----------|--------------------------|-----------|---------------------|
| OECD 301F | 98 %; Oxygen consumption | 28 day(s) | Experimental value |

reaction mass of ethylbenzene and xylene

Biodegradation water

| Method | Value | Duration | Value determination |
|-----------|-----------|-----------|---------------------|
| OECD 301F | 98 %; GLP | 28 day(s) | Experimental value |

Conclusion

Water

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

PT7

Log Kow

| Method | Remark | Value | Temperature | Value determination |
|--------|--------------------------|-------|-------------|---------------------|
| | Not applicable (mixture) | | | |

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Log Kow

| Method | Remark | Value | Temperature | Value determination |
|--------|-------------------|-------|-------------|---------------------|
| | No data available | | | |

reaction mass of ethylbenzene and xylene

BCF fishes

| Parameter | Method | Value | Duration | Species | Value determination |
|-----------|--------|------------|-----------|---------------------|---------------------|
| BCF | | 5.5 - 25.9 | 56 day(s) | Oncorhynchus mykiss | Read-across |

Log Kow

| Method | Remark | Value | Temperature | Value determination |
|----------|--------|-------|-------------|---------------------|
| OECD 117 | | 3.49 | 30 °C | Experimental value |

Conclusion

No straightforward conclusion can be drawn based upon the available numerical values

12.4. Mobility in soil

reaction mass of ethylbenzene and xylene

(log) Koc

| Parameter | Method | Value | Value determination |
|-----------|------------------------|-------|---------------------|
| log Koc | Equivalent to OECD 121 | 2.73 | Read-across |

Conclusion

Contains component(s) with potential for mobility in the soil

PT7

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

PT7

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 01 11* (wastes from MFSU and removal of paint and varnish: waste paint and varnish containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Should not be landfilled with household waste. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

15 01 04 (metallic packaging).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

| | |
|-----------|------|
| UN number | 1950 |
|-----------|------|

14.2. UN proper shipping name

| | |
|----------------------|----------|
| Proper shipping name | aerosols |
|----------------------|----------|

14.3. Transport hazard class(es)

| | |
|------------------------------|--|
| Hazard identification number | |
|------------------------------|--|

| | |
|-------|---|
| Class | 2 |
|-------|---|

| | |
|---------------------|----|
| Classification code | 5F |
|---------------------|----|

14.4. Packing group

| | |
|---------------|--|
| Packing group | |
|---------------|--|

| | |
|--------|-----|
| Labels | 2.1 |
|--------|-----|

14.5. Environmental hazards

| | |
|--|-----|
| Environmentally hazardous substance mark | yes |
|--|-----|

14.6. Special precautions for user

| | |
|--------------------|-----|
| Special provisions | 190 |
|--------------------|-----|

| | |
|--------------------|-----|
| Special provisions | 327 |
|--------------------|-----|

| | |
|--------------------|-----|
| Special provisions | 344 |
|--------------------|-----|

| | |
|--------------------|-----|
| Special provisions | 625 |
|--------------------|-----|

| | |
|--------------------|--|
| Limited quantities | Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) |
|--------------------|--|

Rail (RID)

14.1. UN number

| | |
|-----------|------|
| UN number | 1950 |
|-----------|------|

14.2. UN proper shipping name

| | |
|----------------------|----------|
| Proper shipping name | aerosols |
|----------------------|----------|

14.3. Transport hazard class(es)

| | |
|------------------------------|----|
| Hazard identification number | 23 |
|------------------------------|----|

| | |
|-------|---|
| Class | 2 |
|-------|---|

| | |
|---------------------|----|
| Classification code | 5F |
|---------------------|----|

Reason for revision: 3.2; 8; 9; 12

Publication date: 2010-12-08

Date of revision: 2021-04-14

Revision number: 0400

BIG number: 50486

10 / 13

PT7

| | |
|---|--|
| 14.4. Packing group | |
| Packing group | |
| Labels | 2.1 |
| 14.5. Environmental hazards | |
| Environmentally hazardous substance mark | yes |
| 14.6. Special precautions for user | |
| Special provisions | 190 |
| Special provisions | 327 |
| Special provisions | 344 |
| Special provisions | 625 |
| Limited quantities | Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) |

Inland waterways (ADN)

| | |
|---|--|
| 14.1. UN number | |
| UN number | 1950 |
| 14.2. UN proper shipping name | |
| Proper shipping name | aerosols |
| 14.3. Transport hazard class(es) | |
| Class | 2 |
| Classification code | 5F |
| 14.4. Packing group | |
| Packing group | |
| Labels | 2.1 |
| 14.5. Environmental hazards | |
| Environmentally hazardous substance mark | yes |
| 14.6. Special precautions for user | |
| Special provisions | 190 |
| Special provisions | 327 |
| Special provisions | 344 |
| Special provisions | 625 |
| Limited quantities | Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) |

Sea (IMDG/IMSBC)

| | |
|--|--|
| 14.1. UN number | |
| UN number | 1950 |
| 14.2. UN proper shipping name | |
| Proper shipping name | aerosols |
| 14.3. Transport hazard class(es) | |
| Class | 2.1 |
| 14.4. Packing group | |
| Packing group | |
| Labels | 2.1 |
| 14.5. Environmental hazards | |
| Marine pollutant | P |
| Environmentally hazardous substance mark | yes |
| 14.6. Special precautions for user | |
| Special provisions | 190 |
| Special provisions | 277 |
| Special provisions | 327 |
| Special provisions | 344 |
| Special provisions | 381 |
| Special provisions | 63 |
| Special provisions | 959 |
| Limited quantities | Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) |
| 14.7. Maritime transport in bulk according to IMO instruments | |
| Annex II of MARPOL 73/78 | Not applicable |

Air (ICAO-TI/IATA-DGR)

| | |
|---|---------------------|
| 14.1. UN number | |
| UN number | 1950 |
| 14.2. UN proper shipping name | |
| Proper shipping name | aerosols, flammable |
| 14.3. Transport hazard class(es) | |
| Class | 2.1 |
| 14.4. Packing group | |
| Packing group | |
| Labels | 2.1 |
| 14.5. Environmental hazards | |

PT7

| | |
|--|---------|
| Environmentally hazardous substance mark | yes |
| 14.6. Special precautions for user | |
| Special provisions | A145 |
| Special provisions | A167 |
| Special provisions | A802 |
| Passenger and cargo transport | |
| Limited quantities: maximum net quantity per packaging | 30 kg G |

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

| VOC content | Remark |
|-------------|--------|
| 98.99 % | |
| 699.9 g/l | |

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

| | Designation of the substance, of the group of substances or of the mixture | Conditions of restriction |
|--|--|---|
| · hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane · reaction mass of ethylbenzene and xylene | Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1. | 1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010. |
| · hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane · reaction mass of ethylbenzene and xylene | Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not. | 1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated. |

National legislation Belgium

PT7

No data available

National legislation The Netherlands

PT7

| | |
|----------------------|---|
| Waterbezwaarlijkheid | A (2); Algemene Beoordelingsmethodiek (ABM) |
|----------------------|---|

National legislation France

Reason for revision: 3.2; 8; 9; 12

Publication date: 2010-12-08

Date of revision: 2021-04-14

Revision number: 0400

BIG number: 50486

12 / 13

PT7

PT7

No data available

National legislation Germany

PT7

| | |
|--|--|
| WGK | 2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017 |
| hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane | |
| TA-Luft | 5.2.5 |
| reaction mass of ethylbenzene and xylene | |
| TA-Luft | 5.2.5/I |
| dimethyl ether | |
| TA-Luft | 5.2.5 |

National legislation United Kingdom

PT7

No data available

Other relevant data

PT7

No data available

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs (ears (hearing damage)) through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

| | |
|--------------|--|
| (*) | INTERNAL CLASSIFICATION BY BIG |
| ADI | Acceptable daily intake |
| AOEL | Acceptable operator exposure level |
| ATE | Acute Toxicity Estimate |
| CLP (EU-GHS) | Classification, labelling and packaging (Globally Harmonised System in Europe) |
| DMEL | Derived Minimal Effect Level |
| DNEL | Derived No Effect Level |
| EC50 | Effect Concentration 50 % |
| ErC50 | EC50 in terms of reduction of growth rate |
| LC50 | Lethal Concentration 50 % |
| LD50 | Lethal Dose 50 % |
| NOAEL | No Observed Adverse Effect Level |
| NOEC | No Observed Effect Concentration |
| OECD | Organisation for Economic Co-operation and Development |
| PBT | Persistent, Bioaccumulative & Toxic |
| PNEC | Predicted No Effect Concentration |
| STP | Sludge Treatment Process |
| vPvB | very Persistent & very Bioaccumulative |

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3.2; 8; 9; 12

Publication date: 2010-12-08

Date of revision: 2021-04-14

Revision number: 0400

BIG number: 50486

13 / 13