



Xilicon

SILICONE SPRAY

- ✓ Transparent dry-film lubrication
- ✓ Flawless protection
- ✓ Prevents sticking
- ✓ Water and moisture repelling

Technical Info

- Colour: colourless.
- Odour: slightly paraffin.
- Basis: pure silicone oil.
- Pressure resistance: 1,400 kg/cm².
- Heat-resistance: permanent from -70 °C to +250 °C, with peaks to +280 °C.
- Solubility: insoluble in water, soluble in aliphatic hydrocarbons.
- Shelf life: 36 months kept in a dry, cool and frost-free place.
- Safety measures: Please consult the safety data sheet.

Packing

Xilicon - aerosol 400ml

201012000

Product

Characteristics

The applied film is extremely thin, clear, durable, non-flammable, odourless, smudge-proof and effective on: all metal, rubber, wood, leather, plastic, varnish, paint, fabric, vinyl, etc.

This dry lubricating film does not acidify, does not evaporate, does not harden and prevents freezing.

Due to its pure composition, it is pressure resistant up to 1400 kg/cm² and temperature resistant from -70°C to + 280°C.

Applications

- Lubricates high tech mechanisms and moving parts.
- Protects electrical equipment, synthetic materials, rubber and metal.
- Prevents freezing and sticking of rubber sealings.
- Waterproofs textile, wood and leather.

Use

Spray sparingly at a distance of +/-30 cm. Treated surfaces can be cleaned with Tec7 Cleaner and/or Multiclean.