

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



GALVATECH

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : GALVATECH
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Anti-corrosion agent
Metal surface treatment

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

TEC7*
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@tec7.be
*TEC7 is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Acute	category 1	H400: Very toxic to aquatic life.
Aquatic Chronic	category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2. Label elements



Contains: acetone; hydrocarbons, C9, aromatics; propan-2-ol.

Signal word Danger

H-statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.

P-statements

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)
Technische Schoolstraat 43 A, B-2440 Geel
<http://www.big.be>
© BIG vzw
Reason for revision: 2, 3, 8, 15
Revision number: 0800

Publication date: 2001-05-21
Date of revision: 2023-03-22

BIG number: 33712

1 / 25

878-16433-037-en

GALVATECH

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P280 Wear eye protection.
 P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
dimethyl ether 01-2119472128-37	115-10-6 204-065-8	25% <C<50%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
zinc powder - zinc dust (stabilised) 01-2119467174-37	7440-66-6 231-175-3	25% <C<50%	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(10)	Constituent	M: 1 (Acute, ECHA (registration dossier)) M: 1 (Chronic, ECHA (registration dossier))
acetone 01-2119471330-49	67-64-1 200-662-2	10% <C<25%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	(1)(2)(10)	Constituent	
hydrocarbons, C9, aromatics 01-2119455851-35	128601-23-0 918-668-5	2.5% <C<10%	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411 EUH066	(1)(2)(10)	Constituent	
reaction mass of ethylbenzene and xylene 01-2119486136-34	905-588-0	2.5% <C<10%	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Asp. Tox. 1; H304 STOT RE 2; H373 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	(1)(10)	Constituent	
zinc oxide 01-2119463881-32	1314-13-2 215-222-5	C<2.5%	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(2)	Constituent	M: 1 (Acute, ECHA) M: 1 (Chronic, ECHA)
propan-2-ol 01-2119457558-25	67-63-0 200-661-7	1%<C<2.5%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent	

(1) For H- and EUH-statements in full: see section 16
 (2) Substance with a Community workplace exposure limit
 (10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006
 Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

2 / 25

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Dizziness. Drowsiness.

After skin contact:

ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

After eye contact:

Irritation of the eye tissue.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

Upon combustion CO and CO2 are formed and formation of metal oxides. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill. Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

GALVATECH

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Avoid prolonged and repeated contact with skin.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Keep out of direct sunlight.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

Acetone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1210 mg/m ³
Dimethylether	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1920 mg/m ³

Belgium

Acétone	Time-weighted average exposure limit 8 h	246 ppm
	Time-weighted average exposure limit 8 h	594 mg/m ³
	Short time value	492 ppm
	Short time value	1187 mg/m ³
Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m ³
	Short time value	400 ppm
	Short time value	1000 mg/m ³
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1920 mg/m ³
Zinc (oxyde de) (fraction alvéolaire)	Time-weighted average exposure limit 8 h	2 mg/m ³
	Short time value	10 mg/m ³

The Netherlands

Aceton	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	1210 mg/m ³
	Short time value (Public occupational exposure limit value)	1000 ppm
	Short time value (Public occupational exposure limit value)	2420 mg/m ³
Dimethylether	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	495 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	950 mg/m ³
	Short time value (Public occupational exposure limit value)	781 ppm
	Short time value (Public occupational exposure limit value)	1500 mg/m ³

France

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

4 / 25

GALVATECH

Acétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	500 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	1210 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	1000 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	2420 mg/m ³
Alcool isopropylique	Short time value (VL: Valeur non réglementaire indicative)	400 ppm
	Short time value (VL: Valeur non réglementaire indicative)	980 mg/m ³
Hydrocarbures en C6-C12 (ensemble des vapeurs)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1000 mg/m ³
	Short time value (VL: Valeur non réglementaire indicative)	1500 mg/m ³
Oxyde de diméthyle	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1000 ppm
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1920 mg/m ³
Zinc (oxyde de, fumées)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	5 mg/m ³
Zinc (oxyde de, poussières)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	10 mg/m ³

Germany

Aceton	Time-weighted average exposure limit 8 h (TRGS 900)	500 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1200 mg/m ³
Dimethylether	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1900 mg/m ³
Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	500 mg/m ³

Austria

2-Propanol Kurzzeitwert für Großguss	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m ³
	Kurzzeitwert 30(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 30(Miw) 4x (MAK)	2000 mg/m ³
2-Propanol	Tagesmittelwert (MAK)	200 ppm
	Tagesmittelwert (MAK)	500 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	800 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 mg/m ³
Aceton	Tagesmittelwert (MAK)	500 ppm
	Tagesmittelwert (MAK)	1200 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	4800 mg/m ³
Dimethylether	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1910 mg/m ³
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3820 mg/m ³
Zinkoxid-Rauch	Tagesmittelwert (MAK)	5 mg/m ³

UK

Acetone	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	500 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1210 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	1500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	3620 mg/m ³
Dimethyl ether	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	766 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	958 mg/m ³
Propan-2-ol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	999 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1250 mg/m ³

USA (TLV-ACGIH)

2-propanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
------------	--	---------

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

5 / 25

GALVATECH

2-propanol	Short time value (TLV - Adopted Value)	400 ppm
Acetone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	250 ppm
	Short time value (TLV - Adopted Value)	500 ppm
Zinc oxide	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	2 mg/m ³ (R)
	Short time value (TLV - Adopted Value)	10 mg/m ³ (R)

(R): Respirable fraction

b) National biological limit values

If limit values are applicable and available these will be listed below.

Germany

Aceton (Aceton)	Urin: expositionsende, bzw. schichtende	80 mg/l	
Propan-2-ol (Aceton)	Urin: expositionsende, bzw. schichtende	25 mg/l	
Propan-2-ol (Aceton)	Vollblut: expositionsende, bzw. schichtende	25 mg/l	

USA (BEI-ACGIH)

2-Propanol (Acetone)	Urine: end of shift at end of workweek	40 mg/L	Background, Nonspecific
Acetone (Acetone)	Urine: end of shift	25 mg/L	Nonspecific

8.1.2 Sampling methods

Product name	Test	Number
Acetone (ketones 1)	NIOSH	1300
Acetone (ketones I)	NIOSH	2555
Acetone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
Acetone (Volatile Organic compounds)	NIOSH	2549
Acetone	NIOSH	2027
Acetone	NIOSH	3900
Acetone	NIOSH	8319
Acetone	OSHA	69
Isopropanol (Volatile Organic compounds)	NIOSH	2549
Isopropyl Alcohol (Alcohols I)	NIOSH	1400
Isopropyl Alcohol	NIOSH	3900
Isopropyl Alcohol	OSHA	5001
Zinc & Cpds (as Zn)	NIOSH	7030
Zinc (Elements on wipes)	NIOSH	9102
Zinc (Elements)	NIOSH	7300
Zinc (Elements, aqua regia ashing)	NIOSH	7301
Zinc (Elements, hot block/HCl/HNO ₃ digestion)	NIOSH	7303
Zinc (Zn)	NIOSH	7302
Zinc (Zn)	NIOSH	7304
Zinc (Zn)	NIOSH	7306
Zinc (Zn)	NIOSH	8005
Zinc (Zn)	NIOSH	8200
Zinc (Zn)	NIOSH	8310
Zinc Oxide	NIOSH	7030
Zinc Oxide	NIOSH	7502
Zinc Oxide	OSHA	ID 121
Zinc Oxide	OSHA	ID 143
Zinc	NIOSH	7030
Zinc	OSHA	1006
Zinc	OSHA	ID 121
Zinc	OSHA	ID 125G

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1210 mg/m ³	
	Acute local effects inhalation	2420 mg/m ³	
	Long-term systemic effects dermal	186 mg/kg bw/day	

hydrocarbons, C₉, aromatics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	151 mg/m ³	
	Long-term systemic effects dermal	12.5 mg/kg bw/day	

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

6 / 25

GALVATECH

reaction mass of ethylbenzene and xylene

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	221 mg/m ³	
	Acute systemic effects inhalation	442 mg/m ³	
	Long-term local effects inhalation	221 mg/m ³	
	Acute local effects inhalation	442 mg/m ³	
	Long-term systemic effects dermal	212 mg/kg bw/day	

zinc oxide

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	5 mg/m ³	
	Long-term local effects inhalation	0.5 mg/m ³	
	Long-term systemic effects dermal	83 mg/kg bw/day	

propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m ³	
	Long-term systemic effects dermal	888 mg/kg bw/day	

DNEL/DMEL - General population

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	200 mg/m ³	
	Long-term systemic effects dermal	62 mg/kg bw/day	
	Long-term systemic effects oral	62 mg/kg bw/day	

hydrocarbons, C9, aromatics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	32 mg/m ³	
	Long-term systemic effects dermal	7.5 mg/kg bw/day	
	Long-term systemic effects oral	7.5 mg/kg bw/day	

reaction mass of ethylbenzene and xylene

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	65.3 mg/m ³	
	Acute systemic effects inhalation	260 mg/m ³	
	Long-term local effects inhalation	65.3 mg/m ³	
	Acute local effects inhalation	260 mg/m ³	
	Long-term systemic effects dermal	125 mg/kg bw/day	
	Long-term systemic effects oral	12.5 mg/kg bw/day	

zinc oxide

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2.5 mg/m ³	
	Long-term systemic effects dermal	83 mg/kg bw/day	
	Long-term systemic effects oral	0.83 mg/kg bw/day	

propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m ³	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	

PNEC

zinc powder - zinc dust (stabilised)

Compartments	Value	Remark
Fresh water	14.4 µg/l	Zinc ion
Marine water	7.2 µg/l	Zinc ion
STP	100 µg/l	Zinc ion
Fresh water sediment	146.9 mg/kg sediment dw	Zinc ion
Marine water sediment	162.2 mg/kg sediment dw	Zinc ion
Soil	83.1 mg/kg soil dw	Zinc ion

acetone

Compartments	Value	Remark
Fresh water	10.6 mg/l	
Marine water	1.06 mg/l	
Fresh water (intermittent releases)	21 mg/l	
STP	100 mg/l	
Fresh water sediment	30.4 mg/kg sediment dw	
Marine water sediment	3.04 mg/kg sediment dw	
Soil	29.5 mg/kg soil dw	

GALVATECH

reaction mass of ethylbenzene and xylene

Compartments	Value	Remark
Fresh water	0.327 mg/l	
Salt water	0.327 mg/l	
Fresh water sediment	12.46 mg/kg sediment dw	
Marine water sediment	12.46 mg/kg sediment dw	
Soil	2.31 mg/kg soil dw	
STP	6.58 mg/l	

zinc oxide

Compartments	Value	Remark
Fresh water	20.6 µg/l	Zinc ion
Marine water	6.1 µg/l	Zinc ion
STP	100 µg/l	Zinc ion
Fresh water sediment	117.8 mg/kg sediment dw	Zinc ion
Marine water sediment	56.5 mg/kg sediment dw	Zinc ion
Soil	35.6 mg/kg soil dw	Zinc ion

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Avoid prolonged and repeated contact with skin. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.5 mm	Class 6	

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Solvent-like odour
Odour threshold	No data available in the literature
Colour	Grey
Particle size	Not applicable (aerosol)
Explosion limits	1 - 13 vol % ; Liquid
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	Not applicable (aerosol)
Kinematic viscosity	Not applicable (aerosol)
Melting point	Not applicable (aerosol)
Boiling point	Not applicable (aerosol)
Relative vapour density	No data available in the literature
Vapour pressure	5000 hPa ; 20 °C ; Propellant
Solubility	Water ; insoluble
Relative density	1.04 ; 20 °C
Absolute density	1042 kg/m ³ ; 20 °C
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
pH	Not applicable (aerosol)

9.2. Other information

No data available

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

8 / 25

GALVATECH

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion CO and CO₂ are formed and formation of metal oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

GALVATECH

No (test)data on the mixture available

Judgement is based on the relevant ingredients

zinc powder - zinc dust (stabilised)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 2000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal						Data waiving	
Inhalation (dust)	LD50	OECD 403	> 5.41 mg/l air	4 h	Rat (male / female)	Experimental value	

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		5800 mg/kg		Rat (female)	Experimental value	
Dermal	LD50		> 15800 mg/kg bw	24 h	Rabbit (male)	Experimental value	
					(male)		

hydrocarbons, C9, aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		> 6984 mg/kg bw		Rat (male)	Experimental value	
Oral	LD50		3492 mg/kg bw		Rat (female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 3160 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 6.19 mg/l air	4 h	Rat (male / female)	Experimental value	(maximum achievable concentration)

reaction mass of ethylbenzene and xylene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	EU Method B.1	3523 mg/kg bw		Rat (male)	Experimental value	
Dermal	LD50		> 4200 mg/kg bw	4 h	Rabbit (male)	Experimental value	
Dermal			category 4			Literature study	
Inhalation (vapours)	LC50	Equivalent to EU Method B.2	29.09 mg/l	4 h	Rat (male)	Experimental value	
Inhalation (vapours)			category 4			Literature study	

Classification of this substance is debatable as it does not correspond to the conclusion from the test

GALVATECH

zinc oxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg		Rat (male / female)	Experimental value	
Dermal	LD50	OECD 402	> 2000 mg/kg bw	24 h	Rat (male / female)	Experimental value	
Inhalation (dust)	LC50	Equivalent to OECD 403	> 5.7 mg/l	4 h	Rat (male / female)	Experimental value	

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	16400 ml/kg bw	24 h	Rabbit	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	6 h	Rat (male / female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

GALVATECH

No (test) data on the mixture available

Classification is based on the relevant ingredients

zinc powder - zinc dust (stabilised)

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405	24 h	24; 72 hours	Rabbit	Experimental value	
Skin	Not irritating		5 day(s)		Rabbit	Read-across	
Inhalation	Not irritating	Human observation			Human	Read-across	

acetone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405	24 h	24; 72 hours	Rabbit	Experimental value	Single treatment with rinsing
Skin	Not irritating		3 day(s)	24; 48; 72 hrs; 4 days	Guinea pig	Experimental value	
Inhalation	Slightly irritating	Human observation study	20 minutes		Human	Literature study	

hydrocarbons, C9, aromatics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		1; 24; 48; 72 hours	Rabbit	Experimental value	
Skin	Slightly irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Inhalation (vapours)	Irritating; STOT SE cat.3					Literature study	

reaction mass of ethylbenzene and xylene

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Moderately irritating	Draize Test		24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Eye	Irritating; category 2					Literature study	
Skin	Moderately irritating	Draize Test		24; 72 hours	Rabbit	Experimental value	
Skin	Not corrosive	Equivalent to EU Method B.4	4 h	24; 72 hours	Rabbit	Read-across	
Inhalation (vapours)	Irritating; STOT SE cat.3					Literature study	

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

10 / 25

GALVATECH

zinc oxide

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405	24 h	24; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	OECD 404	24 h	24 hours	Rabbit	Experimental value	
Not applicable (in vitro test)	Not corrosive	OECD 431	3 minutes	24; 72 hours	Reconstructed human epidermis	Experimental value	

propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		1; 2; 3; 4; 7; 10; 14 days	Rabbit	Experimental value	Single treatment without rinsing
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

Conclusion

Causes serious eye irritation.
 Not classified as irritating to the respiratory system
 Not classified as irritating to the skin

Respiratory or skin sensitisation

GALVATECH

No (test)data on the mixture available
 Judgement is based on the relevant ingredients
zinc powder - zinc dust (stabilised)

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (female)	Read-across	

acetone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Guinea pig maximisation test			Guinea pig (female)	Experimental value	
Skin	Not sensitizing	Human observation			Human	Experimental value	

hydrocarbons, C9, aromatics

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (female)	Experimental value	

reaction mass of ethylbenzene and xylene

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal (on the ears)	Not sensitizing	Equivalent to OECD 429			Mouse	Experimental value	

zinc oxide

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (female)	Experimental value	
Skin	Not sensitizing	Human observation	2 days (continuous)	72 hours	Human	Experimental value	

propan-2-ol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

Conclusion

Not classified as sensitizing for skin
 Not classified as sensitizing for inhalation

Specific target organ toxicity

GALVATECH

No (test)data on the mixture available
 Classification is based on the relevant ingredients

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

11 / 25

GALVATECH

zinc powder - zinc dust (stabilised)

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (diet)	NOAEL	OECD 408	31.52 mg/kg bw/day		No effect	13 weeks (daily)	Rat (male / female)	Read-across
Oral (diet)	LOAEL	OECD 408	53.8 mg/kg bw/day	Blood	Change in the haemogramme/blood composition	13 weeks (daily)	Rat (male / female)	Read-across
Dermal								Data waiving
Inhalation (aerosol)	Dose level		0.1 mg/m ³		No effect	16 weeks (6h / day, 5 days / week)	Rat (male)	Read-across

acetone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (drinking water)	NOAEL	Equivalent to OECD 408	4.86 mg/kg bw/day - 5.95 mg/kg bw/day		No effect	13 week(s)	Mouse (male / female)	Experimental value
Oral (drinking water)	LOAEL	Equivalent to OECD 408	11.3 mg/kg bw/day	Liver	Histopathology		Mouse (female)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Subchronic toxicity test	19000 ppm		No effect	8 weeks (5 days / week)	Rat (male)	Experimental value
Inhalation (vapours)	Dose level	Human observation study	361 ppm	Central nervous system	neurotoxic effects	2 day(s)	Human	Epidemiological study

hydrocarbons, C9, aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 408	600 mg/kg bw/day		No effect	13 weeks (daily)	Rat (male / female)	Read-across
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 452	1800 mg/m ³ air		No effect	52 weeks (6h / day, 5 days / week)	Rat (male)	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 452	900 mg/m ³ air		No effect	52 weeks (6h / day, 5 days / week)	Rat (female)	Read-across
Inhalation (vapours)			STOT SE cat.3		Drowsiness, dizziness			Literature study

reaction mass of ethylbenzene and xylene

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Equivalent to EU Method B.32	250 mg/kg bw/day STOT RE cat.2		No effect	103 weeks (daily, 5 days / week)	Rat (male / female)	Experimental value
Unknown			STOT RE cat.2	Hearing organs	Auditory disturbances			Literature study
Inhalation (vapours)	NOAEC	Subchronic toxicity test	≥ 3.52 mg/l		No effect	13 weeks (6h / day, 5 days / week)	Rat (male)	Experimental value

zinc oxide

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (diet)	NOEL	OECD 408	3000 ppm		No effect	13 weeks (daily)	Rat (male / female)	Read-across
Dermal	LOAEL	OECD 410	75 mg/kg bw/day		Systemic effects	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (aerosol)	NOAEL	OECD 413	1.5 mg/m ³ air		No effect	13 weeks (6h / day, 5 days / week)	Rat (male)	Experimental value

propan-2-ol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm		No adverse systemic effects	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)	Dose level	Equivalent to OECD 403	5000 ppm	Central nervous system	Drowsiness, dizziness	6 h	Rat (male / female)	Experimental value

Conclusion

May cause drowsiness or dizziness.

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

12 / 25

GALVATECH

Not classified for subchronic toxicity

Mutagenicity (in vitro)

GALVATECH

No (test) data on the mixture available

Judgement is based on the relevant ingredients

zinc powder - zinc dust (stabilised)

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S. typhimurium and E. coli)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 473	Chinese hamster lung fibroblasts (V79)	No effect	Experimental value	

acetone

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value	

hydrocarbons, C9, aromatics

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

reaction mass of ethylbenzene and xylene

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to EU Method B.10	Chinese hamster ovary (CHO)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to EU Method B.19	Chinese hamster ovary (CHO)		Experimental value	

zinc oxide

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Ambiguous	OECD 476	Mouse (lymphoma L5178Y cells)		Experimental value	

propan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	

Mutagenicity (in vivo)

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

13 / 25

GALVATECH

GALVATECH

No (test) data on the mixture available

Judgement is based on the relevant ingredients

zinc powder - zinc dust (stabilised)

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (aerosol))	OECD 474	2 weeks (6h / day, 5 days / week)	Rat (male / female)		Experimental value

acetone

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (drinking water))	Micronucleus test	13 week(s)	Mouse (male / female)		Literature study

hydrocarbons, C9, aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))	Equivalent to OECD 475	5 days (6h / day)	Rat (male)	Bone marrow	Experimental value

reaction mass of ethylbenzene and xylene

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Subcutaneous)	Equivalent to OECD 478		Mouse (male / female)		Experimental value

zinc oxide

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	OECD 474		Mouse (male)	Bone marrow	Experimental value

propan-2-ol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD 474		Mouse (male / female)		Experimental value

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

GALVATECH

No (test) data on the mixture available

Judgement is based on the relevant ingredients

zinc powder - zinc dust (stabilised)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Oral (drinking water)	NOAEL	Carcinogenic toxicity study	≥ 22000 mg/l	52 weeks (daily)	Mouse (male / female)	No carcinogenic effect		Read-across

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOEL	Carcinogenic toxicity study	79 mg		Mouse (female)	No carcinogenic effect		Literature study

hydrocarbons, C9, aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Unknown								Data waiving

reaction mass of ethylbenzene and xylene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Oral (stomach tube)	Dose level	Equivalent to EU Method B.32	500 mg/kg bw/day	103 weeks (5 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

zinc oxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Oral (drinking water)	NOAEL	Carcinogenic toxicity study	> 22000 mg/l	52 week(s)	Mouse (male / female)	No carcinogenic effect		Read-across

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOEL	OECD 451	5000 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

GALVATECH

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

14 / 25

GALVATECH

No (test) data on the mixture available

Judgement is based on the relevant ingredients

zinc powder - zinc dust (stabilised)

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Developmental toxicity study	42.5 mg/kg bw/day	10 day(s)	Rat	No effect		Read-across
Maternal toxicity (Oral (stomach tube))	NOAEL	Developmental toxicity study	42.5 mg/kg bw/day	10 day(s)	Rat	No effect		Read-across
Effects on fertility (Oral (stomach tube))	LOAEL	Equivalent to OECD 416	7.5 mg/kg bw/day		Rat (male / female)	Reproductive performance		Read-across

acetone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (aerosol))	NOAEC	Equivalent to OECD 414	2200 ppm	14 days (gestation, daily)	Rat	No effect	Foetus	Experimental value
	LOAEC	Equivalent to OECD 414	11000 mg/kg bw/day	14 days (gestation, daily)	Rat	Fetotoxicity	Foetus	Experimental value
Maternal toxicity (Inhalation (aerosol))	NOAEC	Equivalent to OECD 414	2200 ppm	14 days (gestation, daily)	Rat	No effect		Experimental value
	LOAEC	Equivalent to OECD 414	11000 ppm	14 days (gestation, daily)	Rat	Maternal toxicity		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL		900 mg/kg bw/day	13 week(s)	Rat (male)	No effect		Experimental value
	LOAEL		3400 mg/kg bw/day	13 week(s)	Rat (male)	Adverse effects on fertility	Male reproductive organ	Experimental value

hydrocarbons, C9, aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Developmental toxicity study	100 ppm	10 days (6h / day)	Mouse	No effect		Experimental value
	LOAEC	Developmental toxicity study	500 ppm	10 days (6h / day)	Mouse	Reduced fetal bodyweights	Foetus	Experimental value
Maternal toxicity (Inhalation (vapours))	NOAEC	Developmental toxicity study	100 ppm	10 day(s)	Mouse	No effect		Experimental value
	LOAEC	Developmental toxicity study	500 ppm	10 day(s)	Mouse	Body weight reduction	General	Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC	3 generation study	7500 mg/m ³		Rat (male / female)	No effect		Experimental value

reaction mass of ethylbenzene and xylene

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	BMCL10	Equivalent to OECD 414	1082 ppm	15 days (gestation, 6h / day)	Rat	Reduced fetal bodyweights	Foetus	Experimental value
Maternal toxicity (Inhalation (vapours))	BMCL10	Equivalent to OECD 414	887 mg/kg bw/day	15 days (gestation, 6h / day)	Rat	Body weight reduction		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC		500 ppm	> 131 days (6h / day)	Rat (male / female)	No effect		Experimental value

zinc oxide

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (aerosol))	NOAEC	OECD 414	7.5 mg/kg bw/day	14 days (6h / day)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Inhalation (aerosol))	NOAEC	OECD 414	1.5 mg/kg bw/day	14 days (6h / day)	Rat	No effect		Experimental value
Effects on fertility (Oral (stomach tube))	LOAEL (P)	Equivalent to OECD 416	7.5 mg/kg bw/day	22 weeks (daily)	Rat (male / female)	Reproductive performance		Read-across

propan-2-ol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	Equivalent to OECD 415	853 mg/kg bw/day		Rat (male / female)	No effect		Experimental value

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

15 / 25

GALVATECH

Conclusion

Not classified for reprotoxic or developmental toxicity

Aspiration hazard

Judgement is based on the relevant ingredients

Not classified for aspiration toxicity

Toxicity other effects

GALVATECH

Classification is based on the relevant ingredients

acetone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Skin				Skin	Skin dryness or cracking			Literature study

hydrocarbons, C9, aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
				Skin	Skin dryness or cracking			Literature study

Conclusion

Repeated exposure may cause skin dryness or cracking.

Chronic effects from short and long-term exposure

GALVATECH

No effects known.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

GALVATECH

No (test) data on the mixture available

Classification is based on the relevant ingredients

zinc powder - zinc dust (stabilised)

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	ASTM E729-88	0.169 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Zinc ion
Acute toxicity crustacea	EC50	OECD 202	416 µg/l	48 h	Ceriodaphnia dubia	Static system	Fresh water	Experimental value; Zinc ion
Toxicity algae and other aquatic plants	IC50	OECD 201	0.150 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; Zinc ion
	NOEC	OECD 201	0.050 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; Zinc ion
Long-term toxicity fish	NOEC	US EPA	85 µg/l	7 day(s)	Pimephales promelas	Semi-static system	Fresh water	Experimental value; Zinc ion
Long-term toxicity aquatic crustacea	NOEC	US EPA	0.025 mg/l - 0.050 mg/l	1 week(s)	Ceriodaphnia dubia	Semi-static system	Fresh water	Experimental value; Zinc ion
Toxicity aquatic micro-organisms	IC50	ISO 9509:2006	0.35 mg/l	4 h	Activated sludge	Static system	Fresh water	Experimental value; Zinc ion

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

16 / 25

GALVATECH

acetone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	6210 mg/l - 8120 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Measured concentration
Acute toxicity crustacea	LC50		8800 mg/l	48 h	Daphnia pulex	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	NOEC		530 mg/l		Algae		Fresh water	
Long-term toxicity aquatic crustacea	NOEC	Equivalent to OECD 211	2212 mg/l	28 day(s)	Daphnia magna	Flow-through system	Fresh water	Experimental value
Toxicity aquatic micro-organisms	EC50	Equivalent to OECD 209	61.15 g/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value
	EC50		1700 mg/l		Pseudomonas putida			Literature study; Inhibition

hydrocarbons, C9, aromatics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	9.2 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	OECD 202	3.2 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	EL50	OECD 201	2.9 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
	NOEC	OECD 201	0.07 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOELR		1.228 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR
Long-term toxicity aquatic crustacea	NOELR		2.144 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR

reaction mass of ethylbenzene and xylene

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	2.6 mg/l	96 h	Oncorhynchus mykiss	Static renewal	Fresh water	Read-across; Specific isomer
Acute toxicity crustacea	IC50	OECD 202	2.2 mg/l	24 h	Daphnia magna	Static system	Fresh water	Read-across; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	4.4 mg/l	73 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Read-across; GLP
	EC10	OECD 201	1.9 mg/l	73 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Read-across; Growth rate
Long-term toxicity fish	NOEC		> 1.3 mg/l	56 day(s)	Oncorhynchus mykiss	Flow-through system	Fresh water	Read-across; Lethal
Long-term toxicity aquatic crustacea	NOEC	OECD 211	1.6 mg/l	21 day(s)	Daphnia magna	Static renewal	Fresh water	Read-across; GLP

zinc oxide

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	ASTM E729-88	0.169 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Read-across; Zinc ion
Acute toxicity crustacea	EC50	OECD 202	1 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Zinc ion
Toxicity algae and other aquatic plants	IC50	OECD 201	0.136 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Zinc ion
	NOEC	OECD 201	0.024 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Zinc ion
Long-term toxicity fish	NOEC		0.044 mg/l		Pisces			Literature study; Zinc ion
Long-term toxicity aquatic crustacea	NOEC	OECD 211	0.04 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Read-across; Zinc ion
Toxicity aquatic micro-organisms	EC50	OECD 209	> 1000 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; Zinc ion

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

17 / 25

GALVATECH

propan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	9640 mg/l - 10000 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	Toxicity threshold		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea	NOEC		2344 µmol/l	16 day(s)	Daphnia magna		Fresh water	Experimental value; Growth
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	1050 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Toxicity test
	EC50	ISO 8192	41676 mg/l	30 minutes	Activated sludge			Experimental value

Conclusion

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

acetone

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	90.9 %	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	52.431 day(s)	1.5E6 /cm ³	Calculated value

hydrocarbons, C9, aromatics

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	78 %	28 day(s)	Experimental value

reaction mass of ethylbenzene and xylene

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	90 % - 98 %; Oxygen consumption	28 day(s)	Experimental value

propan-2-ol

Biodegradation water

Method	Value	Duration	Value determination
EU Method C.5	53 %; Oxygen consumption	5 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	17.668 h	1.5E6 /cm ³	Calculated value

Conclusion

Water

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

GALVATECH

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

zinc powder - zinc dust (stabilised)

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		0.002; Zinc ion	40 day(s)	Danio rerio	Experimental value

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (inorganic)			

GALVATECH

acetone

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		0.69		Pisces	Literature study

Log Kow

Method	Remark	Value	Temperature	Value determination
		-0.23		Test data

hydrocarbons, C9, aromatics

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBAF v3.01	39.8 l/kg - 177.8 l/kg; Fresh weight		Pisces	QSAR

Log Kow

Method	Remark	Value	Temperature	Value determination
KOWWIN		2.92 - 3.59	20 °C	QSAR

reaction mass of ethylbenzene and xylene

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		7.2 - 25.9	56 day(s)	Oncorhynchus mykiss	Read-across

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		3.5	30 °C	Experimental value

zinc oxide

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (inorganic)			

propan-2-ol

Log Kow

Method	Remark	Value	Temperature	Value determination
		0.05	25 °C	Weight of evidence approach

Conclusion

Does not contain bioaccumulative component(s)

12.4. Mobility in soil

acetone

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.374 - 0.988	Calculated value

hydrocarbons, C9, aromatics

(log) Koc

Parameter	Method	Value	Value determination
log Koc		2.68 - 3.32	QSAR

reaction mass of ethylbenzene and xylene

(log) Koc

Parameter	Method	Value	Value determination
log Koc	OECD 121	2.7	Read-across

zinc oxide

(log) Koc

Parameter	Method	Value	Value determination
log Koc		2.2	Literature study

propan-2-ol

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.185 - 0.541	Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

GALVATECH

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

GALVATECH

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

Groundwater

Groundwater pollutant

acetone

Groundwater

Groundwater pollutant

hydrocarbons, C9, aromatics

Groundwater

Groundwater pollutant

reaction mass of ethylbenzene and xylene

Groundwater

Groundwater pollutant

zinc oxide

Groundwater

Groundwater pollutant

propan-2-ol

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 01 11* (wastes from MFSU and removal of paint and varnish: waste paint and varnish containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Should not be landfilled with household waste. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

UN number	1950
-----------	------

14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

14.3. Transport hazard class(es)

Hazard identification number	
Class	2
Classification code	5F

14.4. Packing group

Packing group	
Labels	2.1

14.5. Environmental hazards

Environmentally hazardous substance mark	yes
--	-----

14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1. UN number

UN number	1950
-----------	------

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

20 / 25

GALVATECH

14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	23
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1. UN number/ID number	
UN number/ID number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	P
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Maritime transport in bulk according to IMO instruments	
Annex II of MARPOL 73/78	Not applicable

Air (ICAO-TI/IATA-DGR)

14.1. UN number/ID number	
UN number/ID number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols, flammable

GALVATECH

14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

Explosives precursors

Due to the presence of one or more components in this mixture, acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

VOC content Directive 2010/75/EU

VOC content	Remark
64.4 %	
671.1 g/l	

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
E1 Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100	200	None	Eco-toxicity
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
<ul style="list-style-type: none"> · acetone · hydrocarbons, C9, aromatics · reaction mass of ethylbenzene and xylene · propan-2-ol 	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
<ul style="list-style-type: none"> · acetone · hydrocarbons, C9, aromatics · reaction mass of ethylbenzene and xylene · propan-2-ol 	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols,

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

22 / 25

GALVATECH

	<p>whether they appear in Part 3 of Annex VI to that Regulation or not.</p>	<ul style="list-style-type: none"> – imitation excrement, – horns for parties, – decorative flakes and foams, – artificial cobwebs, – stink bombs. <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: “For professional users only”.</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>
<ul style="list-style-type: none"> · acetone · propan-2-ol 	<p>Substances falling within one or more of the following points:</p> <p>(a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008:</p> <ul style="list-style-type: none"> – carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation – reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation – skin sensitiser category 1, 1A or 1B – skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 – serious eye damage category 1 or eye irritant category 2 <p>(b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council</p> <p>(c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex.</p> <p>The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.</p>	<p>Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081</p>
<ul style="list-style-type: none"> · zinc powder - zinc dust (stabilised) 	<p>Substances falling within one or more of the following points:</p> <p>(a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008:</p> <ul style="list-style-type: none"> – carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation – reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation – skin sensitiser category 1, 1A or 1B – skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 – serious eye damage category 1 or eye irritant category 2 <p>(b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council</p> <p>(c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex.</p> <p>The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.</p>	<p>Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081</p>

National legislation Belgium
GALVATECH

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

23 / 25

GALVATECH

No data available

propan-2-ol

Agents cancérogènes, mutagènes et reprotoxiques (Code du bien-être au travail, Livre VI, titre 2)	alcool isopropylique; VI.2.2.; Liste des procédés au cours desquels une substance ou un mélange se dégage; Procédé à l'acide fort dans la fabrication d'alcool isopropylique.
---	---

National legislation The Netherlands

GALVATECH

Waterbezwaarlijkheid	A (1); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

National legislation France

GALVATECH

No data available

hydrocarbons, C9, aromatics

Catégorie cancérogène	Hydrocarbures en C6-C12 (ensemble des vapeurs)
Catégorie mutagène	Hydrocarbures en C6-C12 (ensemble des vapeurs)

National legislation Germany

GALVATECH

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017

zinc powder - zinc dust (stabilised)

TA-Luft	5.2.1
---------	-------

acetone

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Aceton; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

hydrocarbons, C9, aromatics

TA-Luft	5.2.5
---------	-------

reaction mass of ethylbenzene and xylene

TA-Luft	5.2.5
---------	-------

zinc oxide

TA-Luft	5.2.1
---------	-------

propan-2-ol

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

National legislation Austria

GALVATECH

No data available

National legislation United Kingdom

GALVATECH

No data available

Other relevant data

GALVATECH

No data available

acetone

TLV - Carcinogen	Acetone; A4
------------------	-------------

propan-2-ol

IARC - classification	3; Isopropanol
TLV - Carcinogen	2-propanol; A4

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

Reason for revision: 2, 3, 8, 15

Publication date: 2001-05-21

Date of revision: 2023-03-22

Revision number: 0800

BIG number: 33712

24 / 25

GALVATECH

H373 May cause damage to organs (ears (hearing damage)) through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
LC0	Lethal Concentration 0 %
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.